SAFETY DATA SHEET



1. Identification

Product identifier NARCOTUN 87XH

Other means of identification

Brand Code 0126

Recommended use For Industrial Use Only

Recommended restrictions None known.

Manufacturer/Supplier information

Manufacturer

Company name HarbisonWalker International

Address 1305 Cherrington Parkway, Suite 100

Moon Township, Pennsylvania 15108 US

Telephone General Phone: 412-375-6600

Website www.thinkHWI.com

Emergency phone number CHEMTREC 24 HOUR 1-800-424-9300

EMERGENCY #

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSkin corrosion/irritationCategory 1

Serious eye damage/eye irritation Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. Causes serious eye damage.

Precautionary statement

Prevention Do not breathe dust. Wash thoroughly after handling. Wear eye/face protection. Wear protective

gloves/protective clothing/eye protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Magnesium Oxide		1309-48-4	60 - 80
Silicon Dioxide		7631-86-9	2.5 - 10
Calcium Oxide		1305-78-8	1 - 2.5

Material name: NARCOTUN 87XH SDS US

Chemical name	Common name and synonyms	CAS number	%
Diiron Trioxide		1309-37-1	1 - 2.5
Silicic Acid, Sodium Salt		1344-09-8	1 - 2.5
Aluminium Oxide (Non-Fibrous)		1344-28-1	0.1 - 1
Methenamine		100-97-0	0.1 - 1
Phenol		108-95-2	0.1 - 1
Chromium		7440-47-3	0 - 0.1
Nickel		7440-02-0	0 - 0.1
Other components below reportable leve	ls		10 - 20

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

blindness could result. Coughing.

Symptoms may be delayed.

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove Eye contact

contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

center immediately.

Ingestion Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Use fire-extinguishing media appropriate for surrounding materials.

Not available.

Not applicable.

Not available.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Collect dust using a vacuum cleaner equipped with HEPA filter.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Avoid the generation of dusts during clean-up. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Calcium Oxide (CAS 1305-78-8)	PEL	5 mg/m3	
Chromium (CAS 7440-47-3)	PEL	1 mg/m3	
Diiron Trioxide (CAS 1309-37-1)	PEL	10 mg/m3	Fume.
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.
Nickel (CAS 7440-02-0)	PEL	1 mg/m3	
US. OSHA Table Z-3 (29 CFR 1910.	1000)		
Components	Type	Value	
Silicon Dioxide (CAS 7631-86-9)	TWA	0.8 mg/m3	
*		20 mppcf	
US. ACGIH Threshold Limit Values			
			_

Components	Туре	Value	Form
Calcium Oxide (CAS 1305-78-8)	TWA	2 mg/m3	
Chromium (CAS 7440-47-3)	TWA	0.5 mg/m3	
Diiron Trioxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.
Nickel (CAS 7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	Form

Components	Type	Value	Form
Calcium Oxide (CAS 1305-78-8)	TWA	2 mg/m3	
Chromium (CAS 7440-47-3)	TWA	0.5 mg/m3	
Diiron Trioxide (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.
Nickel (CAS 7440-02-0)	TWA	0.015 mg/m3	
Silicon Dioxide (CAS 7631-86-9)	TWA	6 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

The resin binder in this product was specifically engineered to have low toxicity, with minimal free-phenol (less than 100ppm in this refractory product) and no free-formaldehyde. Under certain conditions, thermal decomposition products may still include carbon monoxide, carbon dioxide, formaldehyde, phenol and aromatic and/or aliphatic compounds.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Solid Powder.
Color Not available.
Odor Not available.
Odor threshold Not available.
pH Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Material name: NARCOTUN 87XH SDS US

Conditions to avoid

Contact with incompatible materials. Refractories containing crystalline silica may, after service, contain more or less crystalline silica. Care must be taken to avoid and/or control dust from demolition. If in doubt of the proper protection, seek advice from a safety professional. The organic binder in this product falls into a class known as phenolic resin. Refractory products using this type of binder are supplied in two forms, (1) shaped products such as brick and (2) monolithics such as refractory plastics and rams. The hazards associated with phenolic resin are different in the two forms. For pre-cured shapes (brick), the binder has been reacted or polymerized by heat to its solid form prior to shipment. On decomposition by heating, where there is sufficient air and heating rate, the gaseous products are mostly carbon dioxide and water. Under low or limited oxygen supply, decomposition products during heat-up and early service may include phenol, as well as aromatic and/or aliphatic derivatives. After a campaign in service, this refractory product should be completely coked and in that condition the material for disposal would be carbon and an inorganic oxide. During field installation of non-cured unshaped products (monolithics), there is a possibility of exposure to trace amounts of phenol by skin contact and inhalation. After the product has been heated to high temperatures in service, it will have similar decomposition characteristics to pre-cured shapes.

Incompatible materials

Phosphorus. Chlorine.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure. Contact your sales representative for

clarification.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust may irritate respiratory system. Prolonged inhalation may be harmful.

Skin contactCauses severe skin burns.Eye contactCauses serious eye damage.IngestionCauses digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Dusts may irritate the respiratory tract, skin and eyes. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritationCauses severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Chromium (CAS 7440-47-3) 3 Not classifiable as to carcinogenicity to humans. Diiron Trioxide (CAS 1309-37-1) 3 Not classifiable as to carcinogenicity to humans.

Nickel (CAS 7440-02-0) 2B Possibly carcinogenic to humans.

Silicon Dioxide (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Nickel (CAS 7440-02-0) Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - Not

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Material name: NARCOTUN 87XH 0126 Version #: 01 Issue date: 05-22-2015 **Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of this product.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsThis product, in its present state, when discarded or disposed of, is not a hazardous waste

according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Hazardous waste code
Waste from residues / unused

products

Not applicable.

Contaminated packaging

Not available.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

All chemical substances in this product are listed on the TSCA chemical substance inventory

where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Chromium (CAS 7440-47-3) Listed. Nickel (CAS 7440-02-0) Listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

Material name: NARCOTUN 87XH sps us

0126 Version #: 01 Issue date: 05-22-2015

 Chemical name
 CAS number
 % by wt.

 Nickel
 7440-02-0
 0 - 0.1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Chromium (CAS 7440-47-3) Nickel (CAS 7440-02-0)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed

US. Massachusetts RTK - Substance List

Calcium Oxide (CAS 1305-78-8) Chromium (CAS 7440-47-3) Diiron Trioxide (CAS 1309-37-1) Magnesium Oxide (CAS 1309-48-4)

Nickel (CAS 7440-02-0)

Silicon Dioxide (CAS 7631-86-9)

US. New Jersey Worker and Community Right-to-Know Act

Calcium Oxide (CAS 1305-78-8) Chromium (CAS 7440-47-3) Diiron Trioxide (CAS 1309-37-1) Magnesium Oxide (CAS 1309-48-4) Methenamine (CAS 100-97-0) Nickel (CAS 7440-02-0) Silicon Dioxide (CAS 7631-86-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium Oxide (CAS 1305-78-8) Chromium (CAS 7440-47-3) Diiron Trioxide (CAS 1309-37-1) Magnesium Oxide (CAS 1309-48-4) Nickel (CAS 7440-02-0)

Silicon Dioxide (CAS 7631-86-9) **US. Rhode Island RTK**

Chromium (CAS 7440-47-3) Nickel (CAS 7440-02-0)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Nickel (CAS 7440-02-0) Listed: October 1, 1989

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

0126 Version #: 01 Issue date: 05-22-2015

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

05-22-2015 Issue date

Version # 01

Disclaimer This information is based on our present knowledge on creation date. However, this shall not

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

Toxicological Information: Toxicological Data **Revision Information**

Ecological Information: Ecotoxicity

Transport Information: Material Transportation Information

Material name: NARCOTUN 87XH SDS US 8/8

0126 Version #: 01 Issue date: 05-22-2015