SAFETY DATA SHEET



1. Identification

Product identifier HARGATE A 85 P AH

Other means of identification

Brand Code 0354

Recommended use For Industrial Use Only

Users should be informed of the potential presence of respirable dust and respirable crystalline Recommended restrictions

silica as well as their potential hazards. Appropriate training in the proper use and handling of this

material should be provided as required under applicable regulations.

Manufacturer/Supplier information

Manufacturer

Company name HarbisonWalker International

1305 Cherrington Parkway, Suite 100 **Address**

Moon Township, Pennsylvania 15108 US

Telephone General Phone: 412-375-6600

www.thinkHWI.com Website

Emergency phone number CHEMTREC 24 HOUR 1-800-424-9300

EMERGENCY #

2. Hazard(s) identification

Classified hazards

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves/protective clothing/eye protection. Dust may cause cancer.

Label elements

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves/protective clothing/eye protection. Dust may cause cancer.

Hazard(s) not otherwise classified (HNOC)

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves/protective clothing/eye protection. Dust may cause cancer.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aluminium Oxide (Non-Fibrous)		1344-28-1	60 - 80
Kaolin		1332-58-7	2.5 - 10
Kyanite		1302-76-7	2.5 - 10
Orthophosphoric Acid		7664-38-2	2.5 - 10
Silicon Dioxide		7631-86-9	2.5 - 10
Diiron Trioxide		1309-37-1	1 - 2.5

0354 Version #: 01 Issue date: 06-26-2015

Material name: HARGATE A 85 P AH SDS US

Chemical name	Common name and synonyms	CAS number	%
Quartz (SiO2)		14808-60-7	1 - 2.5
Titanium Dioxide		13463-67-7	1 - 2.5
Cristobalite		14464-46-1	0.1 - 1
Other components below reportable I	evels		2.5 - 10

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or Skin contact

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

Ingestion

delayed

Indication of immediate medical attention and special treatment needed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information If concerned: Get medical advice. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Use fire-extinguishing media appropriate for surrounding materials.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Not available.

Specific hazards arising from the chemical

Not applicable.

Special protective equipment and precautions for firefighters Not available.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Material name: HARGATE A 85 P AH 0354 Version #: 01 Issue date: 06-26-2015

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS	PEL	5 mg/m3	Respirable fraction.
344-28-1)		15 mg/m3	Total dust.
Diiron Trioxide (CAS 309-37-1)	PEL	10 mg/m3	Fume.
(aolin (CAS 1332-58-7)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
Orthophosphoric Acid (CAS 7664-38-2)	PEL	1 mg/m3	
Fitanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
JS. OSHA Table Z-3 (29 CFR 1910.	-	Value	Form
Components	Туре	Value	FOIII
Cristobalite (CAS 14464-46-1)	TWA	0.15 mg/m3	Total dust.
		0.05 mg/m3	Respirable.
2 1 . (0:00) (0.10	T10/0	1.2 mppcf	Respirable.
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
1-1000-00-1)		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Silicon Dioxide (CAS 631-86-9)	TWA	0.8 mg/m3	·
·		20 mppcf	
JS. ACGIH Threshold Limit Values Components	s Type	Value	Form
Aluminium Oxide	TWA	1 mg/m3	Respirable fraction.
Non-Fibrous) (CAS			
1344-28-1)	TWA	0.025 mg/m2	Despirable fraction
Cristobalite (CAS 4464-46-1)	IVVA	0.025 mg/m3	Respirable fraction.
Diiron Trioxide (CAS 309-37-1)	TWA	5 mg/m3	Respirable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
(yanite (CAS 1302-76-7)	TWA	1 mg/m3	Respirable fraction.
Orthophosphoric Acid (CAS 7664-38-2)	STEL	3 mg/m3	
(0:00) (0.40	TWA	1 mg/m3	5
Quartz (SiO2) (CAS 4808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Fitanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
JS. NIOSH: Pocket Guide to Chem Components	ical Hazards Type	Value	Form
	TWA	2 fiboro/om2	Eibor
Cristobalite (CAS 4464-46-1)	IWA	3 fibers/cm3	Fiber.
		3 fibers/cm3	Dust.
		5 mg/m3 5 mg/m3	fibers, total dust
		_	Fiber, total
Diiron Trioxide (CAS	Τ\Λ/Δ	5 ma/m3	Dust and fume
	TWA	5 mg/m3	Dust and fume.
Diiron Trioxide (CAS 1309-37-1) Kaolin (CAS 1332-58-7)	TWA TWA	5 mg/m3 5 mg/m3	Dust and fume. Respirable.

US. NIOSH: Pocket Guide to Chemical Hazards			
Components	Туре	Value	Form
Orthophosphoric Acid (CAS 7664-38-2)	STEL	3 mg/m3	
•	TWA	1 mg/m3	
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Silicon Dioxide (CAS 7631-86-9)	TWA	6 mg/m3	

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Solid

Color Not available.

Odor Not available.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower Not a

(%)

Not available.

Flammability limit - upper (%)

Not available.

Explosive limit - lower (%)

Not available.

Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Decomposition temperature Not available. Not available.

Viscosity

Not available.

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Contact with incompatible materials.

Incompatible materials

Acids. Chlorine.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure. Contact your sales representative for

clarification.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes severe skin burns.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica

inhaled from occupational sources can cause lung cancer in humans. However in making the

overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial

circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory

occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and

respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cristobalite (CAS 14464-46-1) 1 Carcinogenic to humans.

Diiron Trioxide (CAS 1309-37-1) 3 Not classifiable as to carcinogenicity to humans.

1 Carcinogenic to humans.

Quartz (SiO2) (CAS 14808-60-7)

Silicon Dioxide (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Cristobalite (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

Not classified.

repeated exposure

Aspiration hazard

Not an aspiration hazard.

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. **Chronic effects**

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

This product, in its present state, when discarded or disposed of, is not a hazardous waste **Disposal instructions**

> according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Hazardous waste code Waste from residues / unused Not available.

Not applicable.

products

Not available. Contaminated packaging

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

All chemical substances in this product are listed on the TSCA chemical substance inventory

where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Orthophosphoric Acid (CAS 7664-38-2) Listed.

SARA 304 Emergency release notification

Not regulated.

Material name: HARGATE A 85 P AH 0354 Version #: 01 Issue date: 06-26-2015

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Aluminium Oxide (Non-Fibrous)	1344-28-1	60 - 80	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)

Cristobalite (CAS 14464-46-1) Diiron Trioxide (CAS 1309-37-1)

Kaolin (CAS 1332-58-7)

Orthophosphoric Acid (CAS 7664-38-2)

Quartz (SiO2) (CAS 14808-60-7) Silicon Dioxide (CAS 7631-86-9)

Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)

Cristobalite (CAS 14464-46-1)

Diiron Trioxide (CAS 1309-37-1)

Kaolin (CAS 1332-58-7)

Orthophosphoric Acid (CAS 7664-38-2)

Quartz (SiO2) (CAS 14808-60-7)

Silicon Dioxide (CAS 7631-86-9)

Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)

Cristobalite (CAS 14464-46-1)

Diiron Trioxide (CAS 1309-37-1)

Kaolin (CAS 1332-58-7)

Orthophosphoric Acid (CAS 7664-38-2)

Quartz (SiO2) (CAS 14808-60-7)

Silicon Dioxide (CAS 7631-86-9)

Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)

Orthophosphoric Acid (CAS 7664-38-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (SiO2) (CAS 14808-60-7) Listed: October 1, 1988

Material name: HARGATE A 85 P AH 0354 Version #: 01 Issue date: 06-26-2015

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

Listed: September 2, 2011

16. Other information, including date of preparation or last revision

06-26-2015 Issue date

Version #

This information is based on our present knowledge on creation date. However, this shall not **Disclaimer**

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

Revision Information Product and Company Identification: Material Attributes

Material name: HARGATE A 85 P AH SDS US 8/8

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).