# SAFETY DATA SHEET



### 1. Identification

Product identifier RENEGADE LA; RENEGADE LA CO-MOLDED

Other means of identification

**Brand Code** 8812, 0506

Recommended use For Industrial Use Only

**Recommended restrictions** Avoid dry cutting, blasting, or dust generation.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HarbisonWalker International

Address 1305 Cherrington Parkway, Suite 100

Moon Township, Pennsylvania 15108 US

**Telephone** General Phone: 412-375-6600

Website www.thinkHWI.com Emergency phone number Not available.

### 2. Hazard(s) identification

#### Classified hazards

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

#### Label elements

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

### Hazard(s) not otherwise classified (HNOC)

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

### 3. Composition/information on ingredients

#### **Mixtures**

| Chemical name                   | Common name and synonyms | CAS number | %         |
|---------------------------------|--------------------------|------------|-----------|
| Magnesium Oxide                 |                          | 1309-48-4  | 80 - 100  |
| Aluminium                       |                          | 7429-90-5  | 2.5 - 10  |
| Aluminium Oxide (Non-Fibrous)   |                          | 1344-28-1  | 2.5 - 10  |
| Carbon Black                    |                          | 1333-86-4  | 2.5 - 10  |
| Graphite                        |                          | 7782-42-5  | 1 - 2.5   |
| Phenol                          |                          | 108-95-2   | 0.1 - 2.5 |
| Ethane-1,2-diol                 |                          | 107-21-1   | < 0.5     |
| Other components below reportab | le levels                |            | 2.5 - 10  |

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Material name: RENEGADE LA; RENEGADE LA CO-MOLDED

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

## 5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media

Not available.

Specific hazards arising from

the chemical

Not applicable.

Special protective equipment and precautions for firefighters

Not available.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

**\**/al...a

Form

For waste disposal, see section 13 of the SDS.

**Environmental precautions** Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and storage

Precautions for safe handling

Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

#### Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components  | Туре  | Value                | Form                       |
|---|-------|----------------------|----------------------------|
| Aluminium (CAS 7429-90-5)                           | PEL   | 5 mg/m3              | Respirable fraction.       |
|   |       | 15 mg/m3             | Total dust.                |
| Aluminium Oxide<br>(Non-Fibrous) (CAS<br>1344-28-1) | PEL   | 5 mg/m3              | Respirable fraction.       |
|   |       | 15 mg/m3             | Total dust.                |
| Carbon Black (CAS<br>1333-86-4)                     | PEL   | 3.5 mg/m3            |                            |
| Graphite (CAS 7782-42-5)                            | PEL   | 5 mg/m3              | Respirable fraction.       |
|   |       | 15 mg/m3             | Total dust.                |
| Magnesium Oxide (CAS 1309-48-4)                     | PEL   | 15 mg/m3             | Total particulate.         |
| US. OSHA Table Z-3 (29 CFR 1910.                    | 1000) |                      |                            |
| Components  | Туре  | Value                | Form                       |
| Aluminium (CAS 7429-90-5)                           | TWA   | 5 mg/m3              | Respirable fraction.       |
|   |       | 15 mg/m3             | Total dust.                |
|   |       | 50 mppcf             | Total dust.                |
|   |       | 15 mppcf             | Respirable fraction.       |
| Aluminium Oxide<br>(Non-Fibrous) (CAS<br>1344-28-1) | TWA   | 5 mg/m3              | Respirable fraction.       |
|   |       |                      |                            |
| ,   |       | 15 mg/m3             | Total dust.                |
| •   |       | 15 mg/m3<br>50 mppcf | Total dust.<br>Total dust. |

SDS US

### US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components  | Туре         | Value     | Form                               |
|---|--------------|-----------|------------------------------------|
|   |              | 15 mppcf  | Respirable fraction.               |
| Graphite (CAS 7782-42-5)                            | TWA          | 15 mppcf  |                                    |
| Magnesium Oxide (CAS<br>1309-48-4)                  | TWA          | 5 mg/m3   | Respirable fraction.               |
|   |              | 15 mg/m3  | Total dust.                        |
|   |              | 50 mppcf  | Total dust.                        |
|   |              | 15 mppcf  | Respirable fraction.               |
| US. ACGIH Threshold Limit Values                    |              |           |                                    |
| Components  | Type         | Value     | Form                               |
| Aluminium (CAS 7429-90-5)                           | TWA          | 1 mg/m3   | Respirable fraction.               |
| Aluminium Oxide<br>(Non-Fibrous) (CAS<br>1344-28-1) | TWA          | 1 mg/m3   | Respirable fraction.               |
| Carbon Black (CAS<br>1333-86-4)                     | TWA          | 3 mg/m3   | Inhalable fraction.                |
| Graphite (CAS 7782-42-5)                            | TWA          | 2 mg/m3   | Respirable fraction.               |
| Magnesium Oxide (CAS<br>1309-48-4)                  | TWA          | 10 mg/m3  | Inhalable fraction.                |
| US. NIOSH: Pocket Guide to Chem                     | ical Hazards |           |                                    |
| Components  | Туре         | Value     | Form                               |
| Aluminium (CAS 7429-90-5)                           | TWA          | 5 mg/m3   | Respirable.                        |
|   |              | 5 mg/m3   | Welding fume or pyrophoric powder. |
|   |              | 10 mg/m3  | Total                              |
| Carbon Black (CAS<br>1333-86-4)                     | TWA          | 0.1 mg/m3 |                                    |
| Graphite (CAS 7782-42-5)                            | TWA          | 2.5 mg/m3 | Respirable.                        |

Biological limit values Exposure guidelines No biological exposure limits noted for the ingredient(s).

The resin binder in this product was specifically engineered to have low toxicity, with minimal free-phenol (less than 100ppm in this refractory product) and no free-formaldehyde. Under certain conditions, thermal decomposition products may still include carbon monoxide, carbon dioxide, formaldehyde, phenol and aromatic and/or aliphatic compounds.

α

Appropriate engineering controls

controis

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

## Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

exceeding the exposure limits.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.





General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### 9. Physical and chemical properties

**Appearance** 

Physical state Solid.

**Form** Brick or Cast Shape Solid.

Not available. Color Odor Not available. **Odor threshold** Not available. Not available. Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Not available. Flash point **Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Explosive limit - lower (%)

Not available.

Not available.

Explosive limit - upper (%) Not available. Not available. Vapor pressure Not available. Vapor density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Not available. **Partition coefficient** 

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Viscosity

Other information

Not explosive. **Explosive properties** Oxidizing properties Not oxidizing.

## 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Material name: RENEGADE LA; RENEGADE LA CO-MOLDED

SDS US 8812, 0506 Version #: 02 Revision date: 04-20-2021 Issue date: 09-04-2015

#### Conditions to avoid

Contact with incompatible materials. Refractories containing crystalline silica may, after service, contain more or less crystalline silica. Care must be taken to avoid and/or control dust from demolition. If in doubt of the proper protection, seek advice from a safety professional.

The organic binder in this product falls into a class known as phenolic resin. Refractory products using this type of binder are supplied in two forms, (1) shaped products such as brick and (2) monolithics/specialties such as refractory plastics and rams. The hazards associated with phenolic resin are different in the two forms. For pre-cured shapes (brick), the binder has been reacted or polymerized by heat to its solid form prior to shipment. On decomposition by heating, where there is sufficient air and heating rate, the gaseous products are mostly carbon dioxide and water. Under low or limited oxygen supply, decomposition products during heat-up and early service may include phenol, as well as aromatic and/or aliphatic derivatives. After a campaign in service, this refractory product should be completely coked and in that condition the material for disposal would be carbon and an inorganic oxide. During field installation of non-cured unshaped products (monolithics), there is a possibility of exposure to trace amounts of phenol by skin contact and inhalation. After the product has been heated to high temperatures in service, it will have similar decomposition characteristics to pre-cured shapes.

Incompatible materials

Strong oxidizing agents.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

### 11. Toxicological information

Information on likely routes of exposure

InhalationNo adverse effects due to inhalation are expected.Skin contactNo adverse effects due to skin contact are expected.Eye contactDirect contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Carbon Black (CAS 1333-86-4) Known To Be Human Carcinogen.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

## 12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** 

This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Hazardous waste code

Since this product is used in several industries, no Waste Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste disposal partner or the

responsible authority.

Waste from residues / unused

products

Not available.

Contaminated packaging

Not available.

### 14. Transport information

DOT

Not regulated as dangerous goods.

ΙΔΤΔ

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

### 15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

### SARA 313 (TRI reporting)

| Chemical name                 | CAS number | % by wt. |  |
|-------------------------------|------------|----------|--|
| Aluminium                     | 7429-90-5  | 2.5 - 10 |  |
| Aluminium Oxide (Non-Fibrous) | 1344-28-1  | 2.5 - 10 |  |

#### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Material name: RENEGADE LA; RENEGADE LA CO-MOLDED

8812, 0506 Version #: 02 Revision date: 04-20-2021 Issue date: 09-04-2015

### **US** state regulations

#### California Proposition 65



WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer, and Ethane-1,2-diol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4) Listed: February 21, 2003

### California Proposition 65 - CRT: Listed date/Developmental toxin

Inventory name

Ethane-1,2-diol (CAS 107-21-1) Listed: June 19, 2015

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Aluminium (CAS 7429-90-5) Carbon Black (CAS 1333-86-4) Magnesium Oxide (CAS 1309-48-4)

#### **International Inventories**

Country(s) or region

| Australia   | Australian Inventory of Chemical Substances (AICS)                     | Yes |
|-------------|--|-----|
| Canada      | Domestic Substances List (DSL)   | Yes |
| Canada      | Non-Domestic Substances List (NDSL)                                    | No  |
| China       | Inventory of Existing Chemical Substances in China (IECSC)             | Yes |
| Europe      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No  |
| Europe      | European List of Notified Chemical Substances (ELINCS)                 | No  |
| Japan       | Inventory of Existing and New Chemical Substances (ENCS)               | No  |
| Korea       | Existing Chemicals List (ECL)  | Yes |
| New Zealand | New Zealand Inventory  | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances              | Yes |

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

### 16. Other information, including date of preparation or last revision

09-04-2015 Issue date **Revision date** 04-20-2021

Version #

This information is based on our present knowledge on creation date. However, this shall not Disclaimer

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

**Revision information** This document has undergone significant changes and should be reviewed in its entirety.

Material name: RENEGADE LA; RENEGADE LA CO-MOLDED

SDS US

On inventory (yes/no)\*

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).