# SAFETY DATA SHEET



#### 1. Identification

Product identifier BOF 932; BOF 932 CO-MOLDED

Other means of identification

**Brand Code** 8841, 974B

Recommended use For Industrial Use Only

Recommended restrictions None known.

Manufacturer/Supplier information

Manufacturer

Company name HarbisonWalker International

Address 1305 Cherrington Parkway, Suite 100

Moon Township, Pennsylvania 15108 US

**Telephone** General Phone: 412-375-6600

Website www.thinkHWI.com

Emergency phone number CHEMTREC 24 HOUR 1-800-424-9300

**EMERGENCY #** 

## 2. Hazard(s) identification

#### Classified hazards

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves/protective clothing/eye protection. Dust may cause cancer.

#### Label elements

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves/protective clothing/eye protection. Dust may cause cancer.

#### Hazard(s) not otherwise classified (HNOC)

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves/protective clothing/eye protection. Dust may cause cancer.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Magnesium Oxide		1309-48-4	60 - 80
Graphite		7782-42-5	10 - 20
Aluminium		7429-90-5	1 - 2.5
Calcium Oxide		1305-78-8	1 - 2.5
Aluminium Oxide (Non-Fibrous)		1344-28-1	0.1 - 1
Phenol		108-95-2	0.1 - 1
Ethane-1,2-diol		107-21-1	0 - 0.1

Material name: BOF 932; BOF 932 CO-MOLDED 8841, 974B Version #: 01 Issue date: 07-15-2015

Chemical name	Common name and synonyms	CAS number	%
Formaldehyde		50-00-0	0 - 0.1
Other components below reportab	le levels		2.5 - 10

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Call a POISON CENTER or doctor/physician.

**Skin contact**Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

blindness could result. Coughing.

**Eye contact** Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

center immediately.

**Ingestion** Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and delayed

uolayou

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under

observation. Symptoms may be delayed.

General information

Take off immediately all contaminated clothing. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves. Show this safety data sheet to

the doctor in attendance.

## 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Use fire-extinguishing media appropriate for surrounding materials.

Not available.

Specific hazards arising from

the chemical

media

Not applicable.

Special protective equipment and precautions for firefighters

Not available.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Stop the flow of material, if this is without risk. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

## 7. Handling and storage

Precautions for safe handling

Minimize dust generation and accumulation. Do not get in eyes, on skin, or on clothing. Avoid breathing dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

Components	for Air Contaminants (29 CFR 1910.10 Type	Value	Form	
Aluminium (CAS 7429-90-5)	PEL	5 mg/m3	Respirable dust.	
		15 mg/m3	Total dust.	
Calcium Oxide (CAS 1305-78-8)	PEL	5 mg/m3		
Graphite (CAS 7782-42-5)	PEL	5 mg/m3	Respirable fraction.	
,		15 mg/m3	Total dust.	
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.	
US. OSHA Table Z-3 (29 CF				
Components	Туре	Value		
Graphite (CAS 7782-42-5)	TWA	15 mppcf		
US. ACGIH Threshold Limit			_	
Components	Туре	Value	Form	
Aluminium (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.	
Calcium Oxide (CAS 1305-78-8)	TWA	2 mg/m3		
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.	
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.	
US. NIOSH: Pocket Guide t	o Chemical Hazards			
Components	Туре	Value	Form	
Aluminium (CAS 7429-90-5)	TWA	5 mg/m3	Welding fume or pyrophoric powder.	
		5 mg/m3	Respirable.	
		10 mg/m3	Total	
Calcium Oxide (CAS 1305-78-8)	TWA	2 mg/m3		
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.	
logical limit values	No biological exposure limits noted for	the ingredient(s).		
osure guidelines	The resin binder in this product was specifically engineered to have low toxicity, with minimal free-phenol (less than 100ppm in this refractory product) and no free-formaldehyde. Under certa conditions, thermal decomposition products may still include carbon monoxide, carbon dioxide, formaldehyde, phenol and aromatic and/or aliphatic compounds.			
propriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.			
-	, such as personal protective equipme			
Eye/face protection	Wear safety glasses with side shields	(or goggles) and a face shield	i.	
Skin protection				
Omn protoction				

# Ind

Wear appropriate chemical resistant gloves. **Hand protection** 

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Respiratory protection Use

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.









General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Solid.
Form Solid

Color Not available.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density

Not available.

Relative density

Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Material name: BOF 932; BOF 932 CO-MOLDED 8841, 974B Version #: 01 Issue date: 07-15-2015

#### Conditions to avoid

Contact with incompatible materials. Refractories containing crystalline silica may, after service, contain more or less crystalline silica. Care must be taken to avoid and/or control dust from demolition. If in doubt of the proper protection, seek advice from a safety professional. The organic binder in this product falls into a class known as phenolic resin. Refractory products using this type of binder are supplied in two forms, (1) shaped products such as brick and (2) monolithics such as refractory plastics and rams. The hazards associated with phenolic resin are different in the two forms. For pre-cured shapes (brick), the binder has been reacted or polymerized by heat to its solid form prior to shipment. On decomposition by heating, where there is sufficient air and heating rate, the gaseous products are mostly carbon dioxide and water. Under low or limited oxygen supply, decomposition products during heat-up and early service may include phenol, as well as aromatic and/or aliphatic derivatives. After a campaign in service, this refractory product should be completely coked and in that condition the material for disposal would be carbon and an inorganic oxide. During field installation of non-cured unshaped products (monolithics), there is a possibility of exposure to trace amounts of phenol by skin contact and inhalation. After the product has been heated to high temperatures in service, it will have similar decomposition characteristics to pre-cured shapes.

Incompatible materials

Phosphorus. Chlorine.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure. Contact your sales representative for

clarification.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

Information on likely routes of exposure

Inhalation Toxic if inhaled.

**Skin contact** Toxic in contact with skin. Causes severe skin burns.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing.

Information on toxicological effects

Acute toxicity Toxic if inhaled. Toxic in contact with skin.

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Persistence and degradability 
No data is available on the degradability of this product.

**Bioaccumulative potential** 

Mobility in soil No data available.

 Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

This product, in its present state, when discarded or disposed of, is not a hazardous waste **Disposal instructions** 

> according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Hazardous waste code Waste from residues / unused

Not applicable. Not available.

products

Contaminated packaging Not available.

### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

# 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA

chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes **Hazard categories** 

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name **CAS** number % by wt. Aluminium 7429-90-5 1 - 2.5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Material name: BOF 932; BOF 932 CO-MOLDED 8841, 974B Version #: 01 Issue date: 07-15-2015

## **US state regulations**

#### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

#### **US. Massachusetts RTK - Substance List**

Aluminium (CAS 7429-90-5) Calcium Oxide (CAS 1305-78-8) Graphite (CAS 7782-42-5) Magnesium Oxide (CAS 1309-48-4)

### US. New Jersey Worker and Community Right-to-Know Act

Aluminium (CAS 7429-90-5) Calcium Oxide (CAS 1305-78-8) Graphite (CAS 7782-42-5) Magnesium Oxide (CAS 1309-48-4)

## US. Pennsylvania Worker and Community Right-to-Know Law

Aluminium (CAS 7429-90-5) Calcium Oxide (CAS 1305-78-8) Graphite (CAS 7782-42-5) Magnesium Oxide (CAS 1309-48-4)

#### **US. Rhode Island RTK**

Aluminium (CAS 7429-90-5)

### **US. California Proposition 65**

This product contains a chemical known to the State of California to cause cancer.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Formaldehyde (CAS 50-00-0) Listed: January 1, 1988

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

07-15-2015 Issue date

Version # 01

This information is based on our present knowledge on creation date. However, this shall not Disclaimer

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

**Revision Information** Product and Company Identification: Product Codes