SAFETY DATA SHEET



1. Identification

Product identifier TZ 452 CASTABLE

Other means of identification

Brand Code 9457

Recommended use For Industrial Use Only

Recommended restrictionsUsers should be informed of the potential presence of respirable dust and respirable crystalline

silica as well as their potential hazards. Appropriate training in the proper use and handling of this

Category 1A

material should be provided as required under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HarbisonWalker International

Address 1305 Cherrington Parkway, Suite 100

Moon Township, Pennsylvania 15108 US

Telephone General Phone: 412-375-6600

Website www.thinkHWI.com

Emergency phone number CHEMTREC 24 HOUR 1-800-424-9300

EMERGENCY #

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental informationBauxite Clays and Zircon Sands may contain trace quantities of naturally occurring radioactive

uranium and thorium (less than or equal to 260 ppm uranium plus 180 ppm thorium = 440 ppm total U + Th or 0.044 % w/w, equivalent to 110 pCi/g or less), and radium (less than or equal to 120 pCi/g). Naturally Occurring Radioactive Material, namely uranium, thorium, and their decay products, including radium, is commonly referred to as "NORM". Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the property use and handling of this material

should be provided as required under applicable regulations.

3. Composition/information on ingredients

Mixtures

Material name: TZ 452 CASTABLE SDS US

Chemical name	Common name and synonyms	CAS number	%
Zircon		14940-68-2	80 - 90
Cement, Alumina, Chemicals		65997-16-2	2.5 - 10
Fumes, Silica		69012-64-2	2.5 - 10
Aluminium Oxide (Non-Fibrous)		1344-28-1	1 - 2.5
Quartz (SiO2)		14808-60-7	0.1 - 1
Other components below reportable	levels		1 - 2.5

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantDirect contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware

of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials.

Not available.

Specific hazards arising from

the chemical

Not applicable.

Special protective equipment and precautions for firefighters

Not available.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Material name: TZ 452 CASTABLE SDS US

US. OSHA Table Z-1 Limits for Components	or Air Contaminants (29 CFR 1910.1000) Type	Value	Form		
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.		
Quartz (SiO2) (CAS	PEL	15 mg/m3 0.05 mg/m3	Total dust.		
14808-60-7) Zircon (CAS 14940-68-2)	PEL	5 mg/m3			
US. OSHA Table Z-3 (29 CFR Components	(1910.1000) Type	Value	Form		
Aluminium Oxide	TWA	5 mg/m3	Respirable fraction.		
(Non-Fibrous) (CAS 1344-28-1)		o mg/mo	respirable mastern.		
		15 mg/m3	Total dust.		
		50 mppcf	Total dust.		
Fumes, Silica (CAS	TWA	15 mppcf 0.8 mg/m3	Respirable fraction.		
69012-64-2)		20 mppcf			
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.		
·		2.4 mppcf	Respirable.		
US. ACGIH Threshold Limit \ Components	√alues Type	Value	Form		
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction.		
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.		
Zircon (CAS 14940-68-2)	STEL	10 mg/m3			
	TWA	5 mg/m3			
US. NIOSH: Pocket Guide to Components	Chemical Hazards Type	Value	Form		
Fumes, Silica (CAS 69012-64-2)	TWA	6 mg/m3			
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.		
Zircon (CAS 14940-68-2)	STEL TWA	10 mg/m3 5 mg/m3			
logical limit values	No biological exposure limits noted for the i	ingredient(s).			
oosure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Occupational exposure to nuisance dust (total and respirable and respirable crystalline silica should be monitored and controlled. Zirconium silicates (zircon sands) contain trace amounts (106-120 pCi/g) of naturally occurring radioactive uranium and thorium. Overexposure by inhalation to respirable dust containing uranium and thorium may cause lung cancer. Eye contact with the dust may cause eye irritation. Measurements made by Dupont during the use of a similar mineral sand indicated the observance of the 5 mg/m3 OSHA PEL for respirable dust and/or the PEL for quartz ensures the user is below the exposure limits established for uranium and thorium. No LD50 or LC50 can be found for zircor sand.				
propriate engineering ntrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.				
ividual protection measures	such as personal protective equipment				
Eye/face protection	If contact is likely, safety glasses with side	shields are recommended	d.		
	If contact is likely, safety glasses with side sometimes. Wear appropriate chemical resistant gloves		1.		

Respiratory protection

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.









General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Solid. Physical state **Form** Solid.

Color Not available. Not available. Odor **Odor threshold** Not available. Not available. рH Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Not available. Flash point **Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Not available. Vapor pressure Vapor density Not available. Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Not available. **Partition coefficient**

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Not explosive. **Explosive properties** Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Material name: TZ 452 CASTABLE

SDS US 9457 Version #: 01 Issue date: 05-15-2015

Incompatible materials Strong oxidizing agents.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is

2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and

respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Fumes, Silica (CAS 69012-64-2) 3 Not classifiable as to carcinogenicity to humans.

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Developmental effects

Quartz (SiO2) 0

Developmental effects - EU category
Quartz (SiO2) 0

Embryotoxicity
Quartz (SiO2) 0

Reproductivity
Quartz (SiO2) 0

Specific target organ toxicity - Not classified.

single exposure

Material name: TZ 452 CASTABLE 9457 Version #: 01 Issue date: 05-15-2015 Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Hazardous waste code

Since this product is used in several industries, no Waste Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste disposal partner or the responsible authority.

Waste from residues / unused

products

Not available.

Contaminated packaging

Not available.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Annex II of MARPOL 73/78 and

the IBC Code

Not applicable.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

9457 Version #: 01 Issue date: 05-15-2015

Material name: TZ 452 CASTABLE SDS US

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. Aluminium Oxide (Non-Fibrous) 1344-28-1 1 - 2.5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

WARNING: This product contains a chemical known to the State of California to cause cancer. **US** state regulations

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Glass, Oxide, Chemicals (CAS 65997-17-3) Listed: July 1, 1990 Quartz (SiO2) (CAS 14808-60-7) Listed: October 1, 1988 Rutile (TiO2) (CAS 1317-80-2) Listed: September 2, 2011 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Quartz (SiO2) (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name On in	ventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No
*A "Yes" indicates that all compo	onents of this product comply with the inventory requirements administered by the governing c	ountry(s)

oduct comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

16. Other information, including date of preparation or last revision

05-15-2015 Issue date

Version # 01

Disclaimer This information is based on our present knowledge on creation date. However, this shall not

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

Revision information Composition / Information on Ingredients: Ingredients

Material name: TZ 452 CASTABLE SDS US