SAFETY DATA SHEET



1. Identification

Product identifier EXPRESS-60 Z ADTECH; EXPRESS-60 Z ADTECH WF

Other means of identification

Brand Code 0762, 448B, 048i

Recommended use For Industrial or Professional Use Only **Recommended restrictions** Avoid dry cutting, blasting, or dust generation.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

HarbisonWalker International Company name

1305 Cherrington Parkway, Suite 100 **Address**

Moon Township, Pennsylvania 15108 US

General Phone: 412-375-6600 Telephone

www.thinkHWI.com Website Not available. **Emergency phone number**

2. Hazard(s) identification

Not classified. Physical hazards

Carcinogenicity Category 1A **Health hazards**

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Danger Signal word

Hazard statement May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Store away from incompatible materials. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal**

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Users should be informed of the potential presence of respirable dust and respirable crystalline

silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and

handling of this material should be provided as required under applicable regulations.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Mullite		1302-93-8	50 - 70
Amorphous Silica	Fumed Silica Silica, crystalline free	7631-86-9	10 - 25
Aluminium Oxide (Non-Fibrous)		1344-28-1	2.5 - 10
Cement, Alumina, Chemica	ls	65997-16-2	2.5 - 10

Material name: EXPRESS-60 Z ADTECH; EXPRESS-60 Z ADTECH WF

Chemical name	Common name and synonyms	CAS number	%
Fumes, Silica		69012-64-2	2.5 - 10
Kyanite		1302-76-7	2.5 - 10
Zircon		14940-68-2	2.5 - 10
Titanium Dioxide		13463-67-7	1 - 2.5
Quartz (SiO2)		14808-60-7	0.1 - 2.5
Cristobalite		14464-46-1	< 0.5
Other components below rep	ortable levels		0.1 - 2.5

Crystalline silica may be present at low concentrations; most of this is encapsulated in the coarse aggregate or as part of the clays or sands.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. Most important Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and delayed

Indication of immediate

Provide general supportive measures and treat symptomatically. Keep victim under observation. medical attention and special Symptoms may be delayed. treatment needed

5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media

Not available.

Specific hazards arising from

the chemical

Not applicable.

Special protective equipment and precautions for firefighters Not available.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.

JS. OSHA Table Z-1 Limits for Ai Components	Type	Value	Form
		15 mg/m3	Total dust.
ristobalite (CAS 4464-46-1)	PEL	0.05 mg/m3	Respirable dust.
Quartz (SiO2) (CAS 4808-60-7)	PEL	0.05 mg/m3	Respirable dust.
itanium Dioxide (CAS 3463-67-7)	PEL	15 mg/m3	Total dust.
Circon (CAS 14940-68-2)	PEL	5 mg/m3	
S. OSHA Table Z-3 (29 CFR 1910 omponents	0.1000) Type	Value	Form
luminium Oxide Non-Fibrous) (CAS 344-28-1)	TWA	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
morphous Silica (CAS 331-86-9)	TWA	0.8 mg/m3	
		20 mppcf	
ristobalite (CAS 1464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
umes, Silica (CAS 9012-64-2)	TWA	0.8 mg/m3	
		20 mppcf	
uartz (SiO2) (CAS 4808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
tanium Dioxide (CAS 3463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
S. ACGIH Threshold Limit Value omponents	s Type	Value	Form
luminium Oxide Non-Fibrous) (CAS 344-28-1)	TWA	1 mg/m3	Respirable fraction.
ristobalite (CAS 4464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
yanite (CAS 1302-76-7)	TWA	1 mg/m3	Respirable fraction.
ullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
uartz (SiO2) (CAS 4808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
tanium Dioxide (CAS 3463-67-7)	TWA	10 mg/m3	
ircon (CAS 14940-68-2)	STEL	10 mg/m3	
	TWA	5 mg/m3	
S. NIOSH: Pocket Guide to Cher omponents	nical Hazards Type	Value	Form
morphous Silica (CAS	TWA	6 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards Form Components Value Type Cristobalite (CAS **TWA** 0.05 mg/m3 Respirable dust. 14464-46-1) Fumes, Silica (CAS **TWA** 6 mg/m3 69012-64-2) Respirable dust. Quartz (SiO2) (CAS **TWA** 0.05 mg/m3 14808-60-7) Zircon (CAS 14940-68-2) STEL 10 mg/m3 **TWA** 5 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

Zirconium silicates (zircon sands) contain trace amounts (106-120 pCi/g) of naturally occurring radioactive uranium and thorium. Overexposure by inhalation to respirable dust containing uranium and thorium may cause lung cancer. Eye contact with the dust may cause eye irritation. Measurements made by Dupont during the use of a similar mineral sand indicated the observance of the 5 mg/m3 OSHA PEL for respirable dust and/or the PEL for quartz ensures the user is below the exposure limits established for uranium and thorium. No LD50 or LC50 can be found for zircon cand

sar

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.







General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Solid.

Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

er Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Explosive limit - upper (%)Not available.Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Chlorine. Fluorine.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous Silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Cristobalite (CAS 14464-46-1) 1 Carcinogenic to humans.

Fumes, Silica (CAS 69012-64-2) 3 Not classifiable as to carcinogenicity to humans.

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Cristobalite (CAS 14464-46-1) Cancer Quartz (SiO2) (CAS 14808-60-7) Cancer **US. National Toxicology Program (NTP) Report on Carcinogens**

Cristobalite (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Developmental effects

0 Quartz (SiO2) **Developmental effects - EU category**

Quartz (SiO2)

Embryotoxicity

Quartz (SiO2) 0 Reproductivity

Not classified.

Quartz (SiO2) 0

Specific target organ toxicity single exposure

repeated exposure

Specific target organ toxicity -Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

No data available. Bioaccumulative potential No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product, in its present state, when discarded or disposed of, is not a hazardous waste

> according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Since this product is used in several industries, no Waste Code can be provided by the supplier. Hazardous waste code

The Waste Code should be determined in arrangement with your waste disposal partner or the

responsible authority.

Waste from residues / unused

products

Not available. Contaminated packaging

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Not applicable. Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not available.

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Cristobalite (CAS 14464-46-1) Cancer Quartz (SiO2) (CAS 14808-60-7) Cancer Cristobalite (CAS 14464-46-1) lung effects Quartz (SiO2) (CAS 14808-60-7) lung effects

Cristobalite (CAS 14464-46-1) immune system effects Quartz (SiO2) (CAS 14808-60-7) immune system effects kidnev effects

Cristobalite (CAS 14464-46-1) kidney effects Quartz (SiO2) (CAS 14808-60-7)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Carcinogenicity

categories

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Aluminium Oxide (Non-Fibrous)	1344-28-1	2.5 - 10	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Titanium Dioxide: Titanium Dioxide, which is

known to the State of California to cause cancer. For more information go

to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

 Quartz (SiO2) (CAS 14808-60-7)
 Listed: October 1, 1988

 Rutile (TiO2) (CAS 1317-80-2)
 Listed: September 2, 2011

 Titanium Dioxide (CAS 13463-67-7)
 Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Cristobalite (CAS 14464-46-1) Quartz (SiO2) (CAS 14808-60-7) Titanium Dioxide (CAS 13463-67-7)

International Inventories

Philippines

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

Philippine Inventory of Chemicals and Chemical Substances (PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory No *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

 Issue date
 06-05-2015

 Revision date
 09-10-2019

Version # 02

Disclaimer This information is based on our present knowledge on creation date. However, this shall not

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: EXPRESS-60 Z ADTECH; EXPRESS-60 Z ADTECH WF

SDS US

On inventory (yes/no)*

No

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).