# SAFETY DATA SHEET



## 1. Identification

**Product identifier RESERV** 

Other means of identification

**Brand Code** 9464

Recommended use For Industrial Use Only

Avoid dry cutting, blasting, or dust generation. Users should be informed of the potential presence **Recommended restrictions** 

> of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under

applicable regulations.

#### Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HarbisonWalker International

**Address** 1305 Cherrington Parkway, Suite 100

Moon Township, Pennsylvania 15108 US

Telephone General Phone: 412-375-6600

Website www.thinkHWI.com **Emergency phone number** Not available.

## 2. Hazard(s) identification

#### Classified hazards

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

#### Label elements

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

#### Hazard(s) not otherwise classified (HNOC)

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Chromium (III) oxide		1308-38-9	50 - 70
Aluminium Oxide (Non-Fibro	ous)	1344-28-1	30 - 50
Amorphous Silica	Fumed Silica Silica, crystalline free	7631-86-9	1 - 2.5
Magnesium Oxide		1309-48-4	1 - 2.5
Kaolin		1332-58-7	0.1 - 2.5
Quartz (SiO2)	•	14808-60-7	< 0.5
Other components below reportable levels			2.5 - 10

## 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

Material name: RESERV SDS US **Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantDirect contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

## 5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media

Not available.

Specific hazards arising from

the chemical

Not applicable.

Special protective equipment and precautions for firefighters

Not available.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places

where dust is formed. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

## Occupational exposure limits

Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Chromium (III) oxide (CAS 1308-38-9)	PEL	0.5 mg/m3	
Kaolin (CAS 1332-58-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.
Quartz (SiO2) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR 1910	0.1000)		
Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Amorphous Silica (CAS 7631-86-9)	TWA	0.8 mg/m3	

Material name: RESERV

9464 Version #: 01 Issue date: 10-20-2020

name: RESERV sps.us

TIC VCTV	Table 7 2	/20 CED	1910.1000)
US. USHA	l able 2-3	123 656	1310.10001

Magnesium Oxide (CAS   TWA   1 mg/m3   Total dust.   15 mg/m3   Respirable fraction.   15 mg/m3   Respirable fraction.   15 mg/m3   Respirable fraction.   15 mg/m3   Total dust.   15 mppcf   Respirable fraction.   15 mppcf   Respirable fraction.   15 mppcf   Respirable fraction.   15 mppcf   Respirable.   15 mppcf	Components	Type	Value	Form
Magnesium Oxide (CAS TWA 5 mg/m3 Total dust. 15 mppcf Respirable fraction 1309-48-4)  Magnesium Oxide (CAS TWA 5 mg/m3 Respirable fraction 15 mppcf Total dust. 15 mppcf Respirable fraction 15 mppcf Total dust. 15 mppcf Respirable fraction 15 mppcf Total dust. 50 mppcf Total dust. 15 mppcf Respirable fraction 15 mppcf Respirable fraction 15 mppcf Respirable fraction 15 mppcf Respirable fraction 14 mg/m3 Respirable fraction 14 mg/m3 Respirable fraction 14 mg/m3 Respirable.  US. ACGIH Threshold Limit Values  Components Type Value Form  Aluminium Oxide TWA 1 mg/m3 Respirable fraction (Non-Fibrous) (CAS 1344-28-1)  Chromium (III) oxide (CAS TWA 1 mg/m3 Respirable fraction 1309-38-9)  Kaolin (CAS 1332-58-7) TWA 0.003 mg/m3 Inhalable fraction 1309-38-9)  Magnesium Oxide (CAS TWA 10 mg/m3 Inhalable fraction 1309-38-4)  Countz (SIO2) (CAS TWA 0.025 mg/m3 Respirable fraction 14808-60-7)  US. NIOSH: Pocket Guide to Chemical Hazards  Components Type Value Form  Amorphous Silica (CAS TWA 0.5 mg/m3 Respirable fraction 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable fraction 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable fraction 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable fraction 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable fraction 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable fraction 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable dust. 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable cuparts 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable dust. 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable dust. 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable cuparts 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable cuparts 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable cuparts 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable cuparts 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable cuparts 14808-80-7)  Cupartz (SIO2) (CAS TWA 0.5 mg/m3 Respirable cuparts 14808-80-7)  Cupartz (SIO2) (CAS TWA			20 mppcf	
Magnesium Oxide (CAS TWA 5 mg/m3 Respirable fraction 1309-48-4)  TWA 5 mg/m3 Respirable fraction 1309-48-4)  TWA 5 mg/m3 Respirable fraction 1309-48-4)  TWA 5 mg/m3 Total dust. 15 mppcf Respirable fraction 15 mg/m3 Total dust. 15 mg/m5 Total dust. 15 mgpcf Respirable fraction 15 mgpcf Total dust. 15 mgpcf Respirable fraction 15 mgpcf Respirable fraction 14808-60-7)  WS. ACGIH Threshold Limit Values Components Type Value Form  Aluminium Oxide (TWA 1 mg/m3 Respirable fraction 14808-60-7)  WS. ACGIH Threshold Limit Values Components Type Value Form  Aluminium Oxide (TWA 1 mg/m3 Respirable fraction 144-28-1)  Chromium (III) oxide (CAS 1 TWA 1 mg/m3 Respirable fraction 1309-38-9)  Kaolin (CAS 1332-58-7) TWA 0.003 mg/m3 Inhalable fraction 1309-38-9)  WS. MOSH: Pocket Guide to Chemical Hazards Components Type Value Form  WS. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Amorphous Silica (CAS TWA 0.5 mg/m3 Respirable fraction 1309-38-9)  Kaolin (CAS 1332-58-7) TWA 0.05 mg/m3 Respirable fraction 14808-60-7)  WS. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Amorphous Silica (CAS TWA 0.5 mg/m3 Respirable fraction 1009-38-3-8-9)  Kaolin (CAS 1332-58-7) TWA 0.5 mg/m3 Respirable Components Type Value Form  Amorphous Silica (CAS TWA 0.5 mg/m3 Respirable Components Type Value Form  Components TWA 0.5 mg/m3 Respirable Components TWA 0.05 mg/m3 Respirable Components T	Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable fraction.
Magnesium Oxide (CAS 1309-48-4)  TWA 5 mg/m3 Respirable fraction 5 mg/m3 Total dust. 50 mpcf Total dust. 15 mg/m3 Total dust. 15 mg/m3 Total dust. 15 mg/m3 Total dust. 15 mg/m3 Respirable fraction 14008-60-7)  Quartz (SiO2) (CAS 1 TWA 0.1 mg/m3 Respirable fraction 14008-60-7)  US. ACGIH Threshold Limit Values Components Type Value Form  Aluminium Oxide TWA 1 mg/m3 Respirable fraction (Non-Fibrous) (CAS 1344-28-1)  Chromium (III) oxide (CAS 17WA 0.003 mg/m3 Inhalable fraction 1309-38-9)  Kaolin (CAS 1332-58-7) TWA 0.003 mg/m3 Respirable fraction (Nortz) (CAS 1309-38-8)  US. ACGIL TYMA 0.025 mg/m3 Respirable fraction (Non-Fibrous) (CAS 1344-28-1)  Chromium (III) oxide (CAS 17WA 0.025 mg/m3 Respirable fraction (Nortz) (CAS 1309-38-9)  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Amorphous Silica (CAS TWA 0.05 mg/m3 Respirable fraction (Nortz) (CAS 1309-38-9)  Kaolin (CAS 1332-58-7) TWA 0.05 mg/m3 Respirable fraction (Nortz) (CAS 1309-38-9)  Kaolin (CAS 1332-58-7) TWA 0.05 mg/m3 Respirable fraction (Nortz) (CAS 1309-38-9)  Kaolin (CAS 1332-58-7) TWA 0.05 mg/m3 Respirable (Nortz) (CAS 1309-38-9)  Kaolin (CAS 1332-58-7) TWA 0.05 mg/m3 Respirable (Nortz) (CAS 1309-38-9)  Kaolin (CAS 1332-58-7) TWA 0.05 mg/m3 Respirable (Nortz) (Nortz) (CAS 1309-38-9)  Kaolin (CAS 1332-58-7) TWA 0.05 mg/m3 Respirable (Nortz) (Nortz) (CAS 1309-38-9)  Kaolin (CAS 1332-58-7) TWA 0.05 mg/m3 Respirable (Nortz)			15 mg/m3	Total dust.
Magnesium Oxide (CAS 1009-48-4)  TWA 5 mg/m3 Respirable fraction 1509-48-4)  TWA 15 mg/m3 Total dust. 50 mppcf 7 Total dust. 50 mppcf 8 Respirable fraction 14 mg/m3 8 Respirable fraction 14 mg/m3 8 Respirable fraction 14 mg/m3 8 Respirable. 50 mg/m3 8 Respirable. 50 mg/m3 8 Respirable. 50 mg/m3 8 Respirable. 50 mg/m3 8 Respirable fraction 14 mg/m3 8 Respirable fraction 15 mg/m3 9 mg/m3 8 Respirable fraction 15 mg/m3 9 mg/			50 mppcf	Total dust.
1309-48-4)  1309-48-4)  1309-48-4)  1309-48-4)  1309-48-4)  14808-60-7)  14808-60-7)  1308-38-9)  1309-38-9  1309-38-9  1309-38-9  1309-38-9  1309-38-9  1309-38-9  1309-38-9  1309-38-9			15 mppcf	Respirable fraction.
Quartz (SiO2) (CAS TWA 0.1 mg/m3 Respirable fraction (Non-Fibrous) (CAS 1322-58-7) TWA 0.003 mg/m3 Respirable fraction (Non-Fibrous) (CAS 1332-58-7) TWA 0.003 mg/m3 Respirable fraction (Nagnesium Oxide (CAS 1309-48-4) TWA 0.025 mg/m3 Respirable fraction (Nagnesium Oxide (CAS 1309-48-4) TWA 0.025 mg/m3 Respirable fraction (Nagnesium Oxide (CAS 17WA 0.003 mg/m3 Inhalable fraction (Nagnesium Oxide (CAS 17WA 0.003 mg/m3 Inhalable fraction (Nagnesium Oxide (CAS 17WA 0.005 mg/m3 Respirable fraction (Nagnesium Oxide (CAS 17WA 0.025 mg/m3 Respirable fraction (Nagnesium Oxide (CAS 17WA 0.025 mg/m3 Respirable fraction (Nagnesium Oxide (CAS 17WA 0.055 mg/m3 Respirable (Nagnesium Oxide (CAS 17WA 0.55 mg/m3 Respirable (Nagnesium Oxide (Nagn		TWA	5 mg/m3	Respirable fraction.
Quartz (SiO2) (CAS TWA 0.1 mg/m3 Respirable fraction 14808-60-7)  US. ACGIH Threshold Limit Values Components Type Value Form  Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)  Chromium (III) oxide (CAS 1342-8-1)  Kaolin (CAS 1332-58-7) TWA 0.003 mg/m3 Inhalable fraction. 1309-88-4)  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  US. NIOSH: Pocket Guide to Chemical Hazards Components TwA 0.5 mg/m3 Respirable fraction.  US. NIOSH: Pocket Guide to Chemical Hazards Components TwA 0.05 mg/m3 Respirable crystalline Silvales Allous Chemical Exposure Immusione dust (total and respirable) and respirable crystalline Silvales Chemical Exposure Immusione dust (total and respirable) and respirable crystalline Silvale Demonstrate of Components Type Components Typ	,		15 mg/m3	Total dust.
Quartz (SiO2) (CAS 14808-60-7)  US. ACGIH Threshold Limit Values Components Type Value Form  Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Chromium (III) oxide (CAS 1344-28-1) Kaolin (CAS 1332-58-7) TWA  Quartz (SiO2) (CAS TWA Qu			50 mppcf	Total dust.
US. ACGIH Threshold Limit Values Components Type Value Form  Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Chromium (III) oxide (CAS 1308-38-9) Kaolin (CAS 1332-58-7) TWA 0.003 mg/m3 Inhalable fraction. 1308-38-9) Kaolin (CAS 1332-58-7) TWA 0.025 mg/m3 Respirable fraction. 1309-38-4) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Amorphous Silica (CAS TWA 0.5 mg/m3 Respirable fraction. 1308-38-9) Kaolin (CAS 1332-58-7) TWA 0.5 mg/m3 Respirable fraction. 1009-48-4) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Amorphous Silica (CAS TWA 0.5 mg/m3 Respirable. 10 mg/m3 Total 10 mg/m3 Total 10 mg/m3 Respirable. 10 mg/m3 Respirable. 10 mg/m3 Respirable. 10 mg/m3 Respirable. 10 mg/m3 Total Cuartz (SiO2) (CAS TWA 0.05 mg/m3 Respirable dust.  Walue Form  Amorphous Silica (CAS TWA 0.5 mg/m3 Respirable. 10 mg/m3 Total Cuartz (SiO2) (CAS TWA 0.05 mg/m3 Respirable dust.  Walue Form  Amorphous Silica (CAS TWA 0.5 mg/m3 Respirable. 10 mg/m3 Total Cuartz (SiO2) (CAS TWA 0.05 mg/m3 Respirable dust.  Walue Form  Amorphous Silica (CAS TWA 0.5 mg/m3 Respirable out- 10 mg/m3 Total Cuartz (SiO2) (CAS TWA 0.05 mg/m3 Respirable dust.  Walue Form  Amorphous Silica (CAS TWA 0.05 mg/m3 Respirable dust.  Walue Form			15 mppcf	Respirable fraction.
Components Type Value Form  Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Chromium (III) oxide (CAS 1308-38-9) Kaolin (CAS 1332-58-7) TWA 0.003 mg/m3 Inhalable fraction. 1308-38-9) Kaolin (CAS 1332-58-7) TWA 0.025 mg/m3 Respirable fraction. 1309-38-4) Couartz (SiO2) (CAS 14808-60-7)  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Form  TWA 0.5 mg/m3 Respirable fraction. 1309-38-9)  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Form  TWA 0.5 mg/m3 Respirable fraction. 1009-48-4)  US. AIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Form  TWA 0.5 mg/m3 Respirable fraction. 10 mg/m3 Total  Chromium (III) oxide (CAS 1308-38-9)  Kaolin (CAS 1332-58-7) TWA 0.5 mg/m3 Respirable. 10 mg/m3 Total  Quartz (SiO2) (CAS 17WA 0.05 mg/m3 Respirable dust. 10 mg/m3 Total  Quartz (SiO2) (CAS 17WA 0.05 mg/m3 Respirable dust. 10 mg/m3 Total  Quartz (SiO2) (CAS 17WA 0.05 mg/m3 Respirable dust. 10 mg/m3 Total  Quartz (SiO2) (CAS 17WA 0.05 mg/m3 Respirable dust. 10 mg/m3 Total  Quartz (SiO2) (CAS 17WA 0.05 mg/m3 Respirable crystalline siling the monitored and controlled.  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rat should be monitored and controlled.  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rat should be monitored and controlled.  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rat should be mached to conditions. If applicable, use process enclosures, local exhaust vent or other engineering controls to maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels below recommended exposure limit exposure in the processor of the maintain airborne levels below recommended exposure limits have not been established,		TWA	0.1 mg/m3	Respirable.
Type   Value   Form	,		2.4 mppcf	Respirable.
(Non-Fibrous) (CAS 1344-28-1) Chromium (III) oxide (CAS TWA 0.003 mg/m3 Inhalable fraction. 1308-38-9) Kaolin (CAS 1332-58-7) TWA 2 mg/m3 Respirable fraction. 1309-48-4) Quartz (SiO2) (CAS TWA 0.025 mg/m3 Respirable fraction. 1309-48-60-7)  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Amorphous Silica (CAS TWA 0.5 mg/m3 Respirable fraction. 1308-38-9) Kaolin (CAS 1332-58-7) TWA 0.5 mg/m3 Respirable. 10 mg/m3 Total Quartz (SiO2) (CAS TWA 0.5 mg/m3 Respirable. 10 mg/m3 Total 10 mg/m3 Total 10 mg/m3 Respirable dust. 14808-60-7)  Occupational exposure limits noted for the ingredient(s). Occupational exposure on unisance dust (total and respirable) and respirable crystalline siling should be monitored and controlled. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation ratishould be monitored and controlled. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation ratishould be matched to conditions. If applicable, use process enclosures, local exhaust ventilation reproduction were engineering controls to maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels to an acceptable level. Vidual protection measures, such as personal protective equipment Eye/face protection Wear appropriate chemical resistant gloves.  Skin protection Hand protection Hand protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level			Value	Form
1308-38-9  Kaolin (CAS 1332-58-7) TWA 2 mg/m3 Respirable fraction	(Non-Fibrous) (CAS	TWA	1 mg/m3	Respirable fraction.
Magnesium Oxide (CAS 1309-48-4) Quartz (SiO2) (CAS TWA 0.025 mg/m3 Respirable fraction. 1309-48-4)  Value Form    Mamorphous Silica (CAS TWA 0.025 mg/m3 Respirable fraction. 14808-60-7)		TWA	0.003 mg/m3	Inhalable fraction.
1309-48-4) Quartz (SiO2) (CAS TWA 0.025 mg/m3 Respirable fraction 14808-60-7)  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Amorphous Silica (CAS TWA 6 mg/m3 7631-86-9) Chromium (III) oxide (CAS TWA 0.5 mg/m3 Respirable. 100 mg/m3 Total Quartz (SiO2) (CAS TWA 0.05 mg/m3 Respirable. 100 mg/m3 Total Quartz (SiO2) (CAS TWA 0.05 mg/m3 Respirable dust. 100 mg/m3 Respirable d	Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form  Amorphous Silica (CAS 7631-86-9) Chromium (III) oxide (CAS 1308-38-9) Kaolin (CAS 1332-58-7) TWA 5 mg/m3 Respirable. 10 mg/m3 Total Quartz (SiO2) (CAS 14808-60-7) Rojical limit values Rosure guidelines Coropriate engineering throis Rosure guidelines Respirate to nuisance dust (total and respirable) and respirable crystalline siling should be matched to conditions. If applicable, use process enclosures, local exhaust vention or other engineering controls to maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels to an acceptable level.  Wear safety glasses with side shields (or goggles).  Respiratory protection Wear suitable protective clothing. Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level.		TWA	10 mg/m3	Inhalable fraction.
Type		TWA	0.025 mg/m3	Respirable fraction.
Amorphous Silica (CAS TWA 6 mg/m3 7631-86-9) Chromium (III) oxide (CAS TWA 0.5 mg/m3 1308-38-9) Kaolin (CAS 1332-58-7) TWA 5 mg/m3 Respirable.  Quartz (SiO2) (CAS TWA 0.05 mg/m3 Respirable dust.  No biological exposure limits noted for the ingredient(s).  Occupational exposure to nuisance dust (total and respirable) and respirable crystalline sili should be monitored and controlled.  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rat should be matched to conditions. If applicable, use process enclosures, local exhaust ventior other engineering controls to maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels to an acceptable level.  (ividual protection measures, such as personal protective equipment Eye/face protection  Hand protection  Wear appropriate chemical resistant gloves.  Other  Wear suitable protective clothing.  Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level	US. NIOSH: Pocket Guide to	o Chemical Hazards		
Chromium (III) oxide (CAS 1308-38-9)  Kaolin (CAS 1332-58-7)  Kaolin (CAS 1332-58-7)  TWA  5 mg/m3  Respirable.  10 mg/m3  Total  Quartz (SiO2) (CAS 14808-60-7)  Respirable dust.  Occupational exposure limits noted for the ingredient(s).  Occupational exposure to nuisance dust (total and respirable) and respirable crystalline sili should be monitored and controlled.  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rat should be matched to conditions. If applicable, use process enclosures, local exhaust ventior of ther engineering controls to maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels to an acceptable level.  Respiratory protection  Wear appropriate chemical resistant gloves.  Other  Wear suitable protective clothing.  Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level	Components	Туре	Value	Form
TWA 5 mg/m3 Respirable.  Quartz (SiO2) (CAS 1332-58-7)  Respirable dust.  Quartz (SiO2) (CAS 14808-60-7)  Respirable dust.  Occupational exposure limits noted for the ingredient(s).  Occupational exposure to nuisance dust (total and respirable) and respirable crystalline sili should be monitored and controlled.  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rat should be matched to conditions. If applicable, use process enclosures, local exhaust ventior of other engineering controls to maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels to an acceptable level.  Wear safety glasses with side shields (or goggles).  Skin protection  Hand protection  Wear appropriate chemical resistant gloves.  Other  Wear suitable protective clothing.  Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level		TWA	6 mg/m3	
Quartz (SiO2) (CAS TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (CAS 1 TWA 0.05 mg/m3 Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (Masses in the sespirable dust.  10 mg/m3 Total  Quartz (SiO2) (Masses in the sespirable dust.  10 mg/m3 Total  Quartz (SiO2) (Masses in the sespirable dust.  10 mg/m3 Total  Respirable dust.  10 mg/m3 Total  Quartz (SiO2) (Masses in the sespirable dust.  10 ng/m3 Total  Respirable dust.  10 ng/m3 ng/m3 lessified	` ,	TWA	0.5 mg/m3	
Quartz (SiO2) (CAS 14808-60-7)  logical limit values     No biological exposure limits noted for the ingredient(s).     Occupational exposure to nuisance dust (total and respirable) and respirable crystalline sili should be monitored and controlled.     Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rat should be matched to conditions. If applicable, use process enclosures, local exhaust ventior or other engineering controls to maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels to an acceptable level.  ividual protection measures, such as personal protective equipment     Eye/face protection     Wear safety glasses with side shields (or goggles).  Skin protection     Hand protection     Wear appropriate chemical resistant gloves.  Other     Wear suitable protective clothing.  Respiratory protection  Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level	Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable.
logical limit values     Occupational exposure limits noted for the ingredient(s).     Occupational exposure to nuisance dust (total and respirable) and respirable crystalline sili should be monitored and controlled.     Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rat should be matched to conditions. If applicable, use process enclosures, local exhaust ventior of other engineering controls to maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels to an acceptable level.  Wear safety glasses with side shields (or goggles).  Skin protection     Hand protection     Wear appropriate chemical resistant gloves.  Other  Wear suitable protective clothing.  Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level			10 mg/m3	Total
Occupational exposure to nuisance dust (total and respirable) and respirable crystalline sili should be monitored and controlled.  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rate should be matched to conditions. If applicable, use process enclosures, local exhaust vention or other engineering controls to maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels to an acceptable level.  Wear safety glasses with side shields (or goggles).  Skin protection  Hand protection  Wear appropriate chemical resistant gloves.  Other  Wear suitable protective clothing.  Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level.		TWA	0.05 mg/m3	Respirable dust.
should be monitored and controlled.  Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rat should be matched to conditions. If applicable, use process enclosures, local exhaust vention or other engineering controls to maintain airborne levels below recommended exposure limits have not been established, maintain airborne levels to an acceptable level.  ividual protection measures, such as personal protective equipment  Eye/face protection  Wear safety glasses with side shields (or goggles).  Skin protection  Hand protection  Wear appropriate chemical resistant gloves.  Other  Wear suitable protective clothing.  Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level	logical limit values	No biological exposure limits noted	d for the ingredient(s).	
should be matched to conditions. If applicable, use process enclosures, local exhaust vention or other engineering controls to maintain airborne levels below recommended exposure lime exposure limits have not been established, maintain airborne levels to an acceptable level.  ividual protection measures, such as personal protective equipment  Eye/face protection  Wear safety glasses with side shields (or goggles).  Skin protection  Hand protection  Wear appropriate chemical resistant gloves.  Other  Wear suitable protective clothing.  Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level	osure guidelines			spirable crystalline silica
Eye/face protection  Skin protection  Hand protection  Other  Wear suitable protective clothing.  Wear suitable protective respirator if there is a risk of exposure to dust/fume at level.		should be matched to conditions. I or other engineering controls to ma	lf applicable, use process enclosur aintain airborne levels below recon	es, local exhaust ventilation nmended exposure limits. I
Hand protection Wear appropriate chemical resistant gloves.  Other Wear suitable protective clothing.  Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level.				
Other Wear suitable protective clothing.  Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level		Wear appropriate chemical resista	ant aloves.	
Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at level	-		Ŭ	
			snirator if there is a risk of exposur	e to dust/fume at levels
	Troopilatory protection		spirator ir tricic is a risk or exposur	c to dustriallic at levels

Material name: RESERV SDS US

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.





# General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance** 

Physical state Solid.

Form Brick or Cast Shape

Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure.

Material name: RESERV SDS US

No hazardous decomposition products are known.

## 11. Toxicological information

## Information on likely routes of exposure

No adverse effects due to inhalation are expected. Inhalation Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

## Information on toxicological effects

Not available. **Acute toxicity** 

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica Carcinogenicity

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial

circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline

silica should be monitored and controlled. Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous Silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans. Chromium (III) oxide (CAS 1308-38-9) 3 Not classifiable as to carcinogenicity to humans.

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Quartz (SiO2) (CAS 14808-60-7) Cancer **US. National Toxicology Program (NTP) Report on Carcinogens** 

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

**Developmental effects** 

n Quartz (SiO2) **Developmental effects - EU category** Quartz (SiO2) 0 **Embryotoxicity** Quartz (SiO2) 0 Reproductivity Quartz (SiO2) 0

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -Not classified.

repeated exposure

Material name: RESERV SDS US **Aspiration hazard** Not an aspiration hazard.

## 12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil

No data available. No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

This product, in its present state, when discarded or disposed of, is not a hazardous waste **Disposal instructions** 

> according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Hazardous waste code Since this product is used in several industries, no Waste Code can be provided by the supplier.

The Waste Code should be determined in arrangement with your waste disposal partner or the

responsible authority.

Waste from residues / unused

products

As sold, this product is not RCRA hazardous. Final used condition must be evaluated prior to disposal. Dispose of waste product in accordance with Federal, State and Local regulations. The chrome compounds (Cr III) in this product may be altered to a hexavalent compound (Cr VI) under certain use conditions, such as exposure to alkali salts and/or high temperatures. Proper waste testing (such as TCLP)must be done to determine the waste status of used product. Reuse and recycling of chrome Refractories is recommended whenever possible.

Contaminated packaging Not available.

## 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

## 15. Regulatory information

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard **US** federal regulations

Communication Standard, 29 CFR 1910.1200. All chemical substances in this product are listed

on the TSCA chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Quartz (SiO2) (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

Material name: RESERV SDS US 6/79464 Version #: 01 Issue date: 10-20-2020

## SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Aluminium Oxide (Non-Fibrous)	1344-28-1	30 - 50
Chromium (III) oxide	1308-38-9	50 - 70

#### Other federal regulations

# Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Chromium (III) oxide (CAS 1308-38-9)

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

## **US** state regulations

#### **California Proposition 65**



WARNING: This product can expose you to chemicals including Quartz (SiO2), which is known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov.

## California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (SiO2) (CAS 14808-60-7) Listed: October 1, 1988 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Magnesium Oxide (CAS 1309-48-4) Quartz (SiO2) (CAS 14808-60-7)

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

## 16. Other information, including date of preparation or last revision

10-20-2020 Issue date

Version # 01

United States & Puerto Rico

This information is based on our present knowledge on creation date. However, this shall not Disclaimer

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

**Revision information** Product and Company Identification: Product and Company Identification

Composition / Information on Ingredients: Component Summary

Material name: RESERV SDS US

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).