

SAFETY DATA SHEET

1. Identification

Product identifier	BARRICADE BSA72
Other means of identification	
Brand Code	624C
Synonyms	WM-7835
Recommended use	Industrial Refractory Shape For Industrial Use Only
Recommended restrictions	Avoid dry cutting, blasting, or dust generation
Manufacturer/Importer/Supplier/	Distributor information
Manufacturer	
Company name	HarbisonWalker International
Address	1305 Cherrington Parkway, Suite 100
	Moon Township, Pennsylvania 15108 US
Telephone	General Phone: 412-375-6600
Website	www.thinkHWI.com
Emergency phone number	Not available.

2. Hazard(s) identification

Classified hazards

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

Label elements

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

Hazard(s) not otherwise classified (HNOC)

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Magnesium Oxide		1309-48-4	50 - 70
Aluminium		7429-90-5	2.5 - 10
Graphite		7782-42-5	2.5 - 10
Calcium Oxide		1305-78-8	1 - 2.5
PITCH		61789-60-4	1 - 2.5
Phenol		108-95-2	0.1 - 2.5
Other components below reportable le	evels		20 - 40

Composition comments

The resin binder in this product was specifically engineered to have low toxicity, with minimal free-phenol (less than 100ppm in this refractory product) and no free-formaldehyde. Under certain conditions, thermal decomposition products may still include carbon monoxide, carbon dioxide, formaldehyde, phenol and aromatic and/or aliphatic compounds.

4. First-aid measures

Specific hazards arising from

Special protective equipment

containment and cleaning up

7. Handling and storage Precautions for safe handling

Conditions for safe storage, including any incompatibilities

Occupational exposure limits

Calcium Oxide (CAS

Aluminium (CAS 7429-90-5)

Graphite (CAS 7782-42-5)

Magnesium Oxide (CAS

Components

1305-78-8)

1309-48-4)

1309-48-4)

8. Exposure controls/personal protection

Environmental precautions

Personal precautions, protective equipment and emergency procedures Methods and materials for

and precautions for firefighters

6. Accidental release measures

media

the chemical

Inhalation	Move to fresh air. Call a physician if symptome develop or persist
Innalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
5. Fire-fighting measures	
Suitable extinguishing media Unsuitable extinguishing	Use fire-extinguishing media appropriate for surrounding materials. Not available.

For waste disposal, see section 13 of the SDS.

Observe good industrial hygiene practices.

Туре

PEL

PEL

PEL

PEL

Avoid discharge into drains, water courses or onto the ground.

Store away from incompatible materials (see Section 10 of the SDS).

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Value

5 mg/m3

15 mg/m3

5 mg/m3

5 mg/m3

15 mg/m3

15 mg/m3

Form

Total dust.

Total dust.

Respirable fraction.

Respirable fraction.

Total particulate.

Not applicable.

Not available.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

US. OSHA Table Z-3 (29 CFR 1910.1000)			
Components	Туре	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Graphite (CAS 7782-42-5)	TWA	15 mppcf	
Magnesium Oxide (CAS	TWA	5 mg/m3	Respirable fraction.

US. OSHA Table Z-3 (29 CFF Components	Туре	Value	Form
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit			
Components	Туре	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Calcium Oxide (CAS 1305-78-8)	TWA	2 mg/m3	
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Components	Chemical Hazards Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m3	
Aluminium (CAS 7429-90-5)	IWA	5 mg/m3	Respirable. Welding fume or
		10 mg/m3	pyrophoric powder. Total
Calcium Oxide (CAS	TWA	5	TOLAI
1305-78-8)	IWA	2 mg/m3	
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.
logical limit values	No biological exposure limits noted f	or the ingredient(s).	
oosure guidelines	The resin binder in this product was free-phenol (less than 100ppm in this conditions, thermal decomposition pl formaldehyde, phenol and aromatic a	s refractory product) and no fre- roducts may still include carbon	e-formaldehyde. Under certa
propriate engineering htrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
ividual protection measures, Eye/face protection	such as personal protective equipm Wear safety glasses with side shield		
Skin protection			
Hand protection	Wear appropriate chemical resistant	gioves.	
Other Descrimtory protection	Wear suitable protective clothing.	rator if there is a risk of overage	ro to duct/fumo at lovalo
Respiratory protection	Use a NIOSH/MSHA approved respi exceeding the exposure limits.	rator il there is a risk of exposu	re to dust/lume at levels
Thermal hazards	Wear appropriate thermal protective	clothing, when necessary.	
neral hygiene nsiderations	Always observe good personal hygie and before eating, drinking, and/or s		

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Brick or Cast Shape Solid.

equipment to remove contaminants.

Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials. Refractories containing crystalline silica may, after service, contain more or less crystalline silica. Care must be taken to avoid and/or control dust from demolition. If in doubt of the proper protection, seek advice from a safety professional.
	The organic binder in this product falls into a class known as phenolic resin. Refractory products using this type of binder are supplied in two forms, (1) shaped products such as brick and (2) monolithics/specialties such as refractory plastics and rams. The hazards associated with phenolic resin are different in the two forms. For pre-cured shapes (brick), the binder has been reacted or polymerized by heat to its solid form prior to shipment. On decomposition by heating, where there is sufficient air and heating rate, the gaseous products are mostly carbon dioxide and water. Under low or limited oxygen supply, decomposition products during heat-up and early service may include phenol, as well as aromatic and/or aliphatic derivatives. After a campaign in service, this refractory product should be completely coked and in that condition the material for disposal would be carbon and an inorganic oxide. During field installation of non-cured unshaped products (monolithics), there is a possibility of exposure to trace amounts of phenol by skin contact and inhalation. After the product has been heated to high temperatures in service, it will have similar decomposition characteristics to pre-cured shapes.
Incompatible materials	Strong oxidizing agents. Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure.

11. Toxicological information

Information on likely routes of exposure

information on likely routes of e	
Inhalation	No adverse effects due to inhalation are expected.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.
Information on toxicological effe	ects
Acute toxicity	Not available.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitizatior	1
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Not classifiable as to carcinogenicity to humans.
IARC Monographs. Overall I Not listed.	Evaluation of Carcinogenicity
Not regulated. US. National Toxicology Pro Not listed.	d Substances (29 CFR 1910.1001-1052) ogram (NTP) Report on Carcinogens
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
12. Ecological information	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability Bioaccumulative potential	No data is available on the degradability of any ingredients in the mixture.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.
13. Disposal consideration	ns
Disposal instructions	This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.
Hazardous waste code	Since this product is used in several industries, no Waste Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste disposal partner or the responsible authority.
Waste from residues / unused products	Not available.
Contaminated packaging	Not available.

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations	Communication Stand		s Chemical" as defined by th 0. All chemical substances in vhere required.	
TSCA Section 12(b) Export	Notification (40 CFR 7	07, Subpt. D)		
Not regulated. CERCLA Hazardous Substa	ance List (40 CFR 302.4	4)		
Not listed. SARA 304 Emergency relea	ase notification			
Not regulated. OSHA Specifically Regulate Not regulated.	ed Substances (29 CFR	8 1910.1001-1052)		
Superfund Amendments and Re	eauthorization Act of 1	986 (SARA)		
SARA 302 Extremely hazar				
Not listed.				
SARA 311/312 Hazardous chemical	No (Exempt)			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Aluminium		7429-90-5	2.5 - 10	
Other federal regulations				
Clean Air Act (CAA) Section	n 112 Hazardous Air Po	ollutants (HAPs) List		
Not regulated. Clean Air Act (CAA) Section	n 112(r) Accidental Rel	ease Prevention (40 C	FR 68.130)	
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
California Proposition 65				
of ca		cer, and Ethane-1,2-dio er reproductive harm. Fo	ng Benzo(a)pyrene, which is I, which is known to the State or more information go	
California Proposition	65 - CRT: Listed date/C	arcinogenic substanc	e	
		Listed: July 1 er Consumer Product	, 1987 s Regulations (Cal. Code R	egs, tit. 22, 69502.3,
subd. (a))				
Aluminium (CAS 74: Magnesium Oxide (PITCH (CAS 61789:	CAS 1309-48-4)			
International Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	-	of Chemical Substances	(AICS)	No
Canada	Domestic Substances	s List (DSL)		No
Canada	Non-Domestic Substa	ances List (NDSL)		No

Country(s) or region	Inventory name C	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	05-02-2018
Revision date	10-28-2020
Version #	02
Disclaimer	This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.