SAFETY DATA SHEET



1. Identification

Product identifier ARMORTECH 65AL C

Other means of identification

Brand Code 653B

Recommended use For Industrial Use Only

Recommended restrictions Avoid dry cutting, blasting, or dust generation.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

HarbisonWalker International Company name

1305 Cherrington Parkway, Suite 100 **Address**

Moon Township, Pennsylvania 15108 US

General Phone: 412-375-6600 Telephone

www.thinkHWI.com Website Not available. **Emergency phone number**

2. Hazard(s) identification

Not classified. Physical hazards

Carcinogenicity Category 1A **Health hazards**

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Danger Signal word

Hazard statement May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Store away from incompatible materials. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal**

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Users should be informed of the potential presence of respirable dust and respirable crystalline

silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and

handling of this material should be provided as required under applicable regulations.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aluminium Oxide (Non-Fibro	ous)	1344-28-1	30 - 50
Mullite		1302-93-8	30 - 50
Amorphous Silica	Fumed Silica Silica, crystalline free	7631-86-9	2.5 - 10
Barium Sulfate		7727-43-7	2.5 - 10

Material name: ARMORTECH 65AL C 653B Version #: 03 Revision date: 11-16-2022 Issue date: 06-04-2015

Chemical name	Common name and synonyms	CAS number	%
Cement, Alumina, Chemicals		65997-16-2	2.5 - 10
Fumes, Silica		69012-64-2	2.5 - 10
Titanium Dioxide		13463-67-7	1 - 2.5
Cristobalite		14464-46-1	< 0.5
Other components below reportable levels			2.5 - 10

Crystalline silica may be present at low concentrations; most of this is encapsulated in the coarse aggregate or as part of the clays or sands.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantDirect contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials. Not available.

Specific hazards arising from N

the chemical

Not applicable.

Special protective equipment and precautions for firefighters

Not available.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Type	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

Material name: ARMORTECH 65AL C
653B Version #: 03 Revision date: 11-16-2022 Issue date: 06-04-2015

US. OSHA Table Z-1 Limits for Air Components	r Contaminants (29 CFR 1910.1000) Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	PEL	5 mg/m3	Respirable fraction.
·		15 mg/m3	Total dust.
Cristobalite (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910 Components	0.1000) Type	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS	TWA	5 mg/m3	Respirable fraction.
1344-28-1)		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Amorphous Silica (CAS 7631-86-9)	TWA	0.8 mg/m3	respirable fraction.
7001-00-3)		20 mppcf	
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
Fumes, Silica (CAS 69012-64-2)	TWA	0.8 mg/m3	
		20 mppcf	
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Value Components	es Type	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction.
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Cher Components	mical Hazards Type	Value	Form
Amorphous Silica (CAS 7631-86-9)	TWA	6 mg/m3	
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
		10 mg/m3	Total
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
Fumes, Silica (CAS 69012-64-2)	TWA	6 mg/m3	

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelinesOccupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

The resin binder in this product was specifically engineered to have low toxicity, with minimal free-phenol (less than 100ppm in this refractory product) and no free-formaldehyde. Under certain conditions, thermal decomposition products may still include carbon monoxide, carbon dioxide,

formaldehyde, phenol and aromatic and/or aliphatic compounds.

Appropriate engineering controls

exposure limits

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.









General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Solid.

Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

SDS US

Not available. Vapor pressure Not available. Vapor density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available. (n-octanol/water)

Auto-ignition temperature

Not available. Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Not explosive. **Explosive properties Oxidizing properties** Not oxidizing.

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

No dangerous reaction known under conditions of normal use.

Contact with incompatible materials. Refractories containing crystalline silica may, after service, contain more or less crystalline silica. Care must be taken to avoid and/or control dust from demolition. If in doubt of the proper protection, seek advice from a safety professional.

The organic binder in this product falls into a class known as phenolic resin. Refractory products using this type of binder are supplied in two forms, (1) shaped products such as brick and (2) monolithics/specialties such as refractory plastics and rams. The hazards associated with phenolic resin are different in the two forms. For pre-cured shapes (brick), the binder has been reacted or polymerized by heat to its solid form prior to shipment. On decomposition by heating, where there is sufficient air and heating rate, the gaseous products are mostly carbon dioxide and water. Under low or limited oxygen supply, decomposition products during heat-up and early service may include phenol, as well as aromatic and/or aliphatic derivatives. After a campaign in service, this refractory product should be completely coked and in that condition the material for disposal would be carbon and an inorganic oxide. During field installation of non-cured unshaped products (monolithics), there is a possibility of exposure to trace amounts of phenol by skin contact and inhalation. After the product has been heated to high temperatures in service, it will have similar decomposition characteristics to pre-cured shapes.

Incompatible materials Acids, Aluminum, Chlorine, Fluorine, Phosphorus,

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Not available. Acute toxicity

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Material name: ARMORTECH 65AL C

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica Carcinogenicity

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory

occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and

respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous Silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Cristobalite (CAS 14464-46-1) 1 Carcinogenic to humans.

Fumes, Silica (CAS 69012-64-2) 3 Not classifiable as to carcinogenicity to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Cristobalite (CAS 14464-46-1)

US. National Toxicology Program (NTP) Report on Carcinogens Cristobalite (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. **Chronic effects**

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

No data is available on the degradability of any ingredients in the mixture.

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

Mobility in soil

No data available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

This product, in its present state, when discarded or disposed of, is not a hazardous waste **Disposal instructions**

according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Hazardous waste code Since this product is used in several industries, no Waste Code can be provided by the supplier.

The Waste Code should be determined in arrangement with your waste disposal partner or the

responsible authority.

Waste from residues / unused

products

Not available.

Contaminated packaging Not available.

Material name: ARMORTECH 65AL C

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Barium Sulfate (CAS 7727-43-7)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Cristobalite (CAS 14464-46-1) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Carcinogenicity

categories

SARA 313 (TRI reporting)
Chemical name
CAS number % by wt.

Aluminium Oxide (Non-Fibrous) 1344-28-1 30 - 50

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65

WARNING: This product can expose you to chemicals including Titanium Dioxide: Titanium Dioxide, which is

known to the State of California to cause cancer. For more information go

to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (SiO2) (CAS 14808-60-7) Listed: October 1, 1988 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Cristobalite (CAS 14464-46-1) Titanium Dioxide (CAS 13463-67-7)

Material name: ARMORTECH 65AL C

SDS US

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical	No

Substances (EINECS) European List of Notified Chemical Substances (ELINCS) Europe No Inventory of Existing and New Chemical Substances (ENCS) No Japan Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes **Philippines** No

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

06-04-2015 Issue date 11-16-2022 **Revision date**

Version # 03

Disclaimer This information is based on our present knowledge on creation date. However, this shall not

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: ARMORTECH 65AL C SDS US

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).