

# SAFETY DATA SHEET

# 1. Identification

Product identifier	NIKE S65W DC
Other means of identification	
Brand Code	718B
Recommended use	For Industrial Use Only
Recommended restrictions	Avoid dry cutting, blasting, or dust generation. Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.
Manufacturer/Importer/Supplier	/Distributor information
Manufacturer	
Company name	HarbisonWalker International

Company name	HarbisonWalker Internat	ional
Address	1305 Cherrington Parkw	ay, Suite 100
	Moon Township, Pennsy	Ivania 15108 US
Telephone	General Phone:	412-375-6600
Website	www.thinkHWI.com	
Emergency phone number	Not available.	

# 2. Hazard(s) identification

#### **Classified hazards**

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

#### Label elements

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

#### Hazard(s) not otherwise classified (HNOC)

This item is defined as an article per OSHA, REACH, and WHMIS and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not Classified as hazardous. However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. Wear protective gloves/protective clothing/eye protection.

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Mullite		1302-93-8	80 - 100
Aluminium Oxide (Non-Fibro	us)	1344-28-1	2.5 - 10
Amorphous Silica	Fumed Silica Silica, crystalline free	7631-86-9	2.5 - 10
Andalusite (Al2O(SiO4))		12183-80-1	2.5 - 10
Cristobalite		14464-46-1	1 - 2.5
Titanium Dioxide		13463-67-7	1 - 2.5
TRADE SECRET*		Proprietary*	0.1 - 2.5

## 4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
--------------	--

Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible).
5. Fire-fighting measures	
Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	Not available.
Specific hazards arising from the chemical	Not applicable.
Special protective equipment and precautions for firefighters	Not available.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Store away from incompatible materials (see Section 10 of the SDS). Conditions for safe storage,

including any incompatibilities

# 8. Exposure controls/personal protection

### **Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Cristobalite (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 191	0.1000)		
Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

# US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Amorphous Silica (CAS 7631-86-9)	TWA	0.8 mg/m3	
		20 mppcf	
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Lim Components	it Values Type	Value	Form
			-
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction.
Andalusite (Al2O(SiO4)) (CAS 12183-80-1)	TWA	1 mg/m3	Respirable fraction.
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide	to Chemical Hazards		
Components	Туре	Value	Form
Amorphous Silica (CAS 7631-86-9)	TWA	6 mg/m3	
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
logical limit values	No biological exposure limits noted f	or the ingredient(s).	
oosure guidelines	Occupational exposure to nuisance or should be monitored and controlled.	dust (total and respirable) and re	espirable crystalline silica
propriate engineering htrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilatior or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
ividual protection measure Eye/face protection	s, such as personal protective equipm Wear safety glasses with side shield		
Skin protection Hand protection	Wear appropriate chemical resistant	gloves.	
Other	Use of an impervious apron is recom	imended.	
Respiratory protection	Use a NIOSH/MSHA approved respi exceeding the exposure limits.		e to dust/fume at levels
Thermal hazards	Wear appropriate thermal protective	clothing, when necessary.	

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

	•
Appearance	
Physical state	Solid. Brick or Cast Shape Solid.
Form Color	Not available.
Odor	Not available.
Odor threshold	Not available.
	Not available.
pH Malting paint/freezing paint	
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure.
Hazardous decomposition products	No hazardous decomposition products are known.
11. Toxicological informat	ion

## Information on likely routed of experies

### Information on likely routes of exposure Inhalation Prolong

Prolonged inhalation may be harmful.

Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.
Information on toxicological effe	ects
Acute toxicity	Not known.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitizatior	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk" (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica and controlled.
IARC Monographs. Overall I	Evaluation of Carcinogenicity
Amorphous Silica (CAS 7 Cristobalite (CAS 14464- Titanium Dioxide (CAS 13	631-86-9)3 Not classifiable as to carcinogenicity to humans.46-1)1 Carcinogenic to humans.
Cristobalite (CAS 14464- US. National Toxicology Pro	46-1) Cancer gram (NTP) Report on Carcinogens
Cristobalite (CAS 14464-	
Ύ,	Reasonably Anticipated to be a Human Carcinogen.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.
12. Ecological information	
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

Disposal instructions	This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.
Hazardous waste code	Since this product is used in several industries, no Waste Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste disposal partner or the responsible authority.
Waste from residues / unused products	Not available.
Contaminated packaging	Not available.
14. Transport information	

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

# 15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA chemical substance inventory where required.
TSCA Section 12(b) Export N	lotification (40 CFR 707, Subpt, D)

Niet ne svilete d	,	707, Subpt. D)		
Not regulated.	noo Lint /40 CEB 201	D <i>A</i> )		
CERCLA Hazardous Substa	ICE LIST (40 CFR 302	2.4)		
Not listed.	a matification			
SARA 304 Emergency release	se notification			
Not regulated.				
OSHA Specifically Regulate	•	•		
Cristobalite (CAS 14464-4	46-1)	Cancer		
		lung effects		
		immune system effects kidney effects		
		•		
Superfund Amendments and Re		1986 (SARA)		
SARA 302 Extremely hazard	lous substance			
Not listed.				
SARA 311/312 Hazardous chemical	No (Exempt)			
SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Aluminium Oxide (Non-Fi	brous)	1344-28-1	2.5 - 10	
Other federal regulations				
Clean Air Act (CAA) Section	112 Hazardous Air	Pollutants (HAPs) List		
NI CONTRACTOR INTERNAL				
Not regulated.				
Not regulated. Clean Air Act (CAA) Section	112(r) Accidental R	elease Prevention (40 CI	FR 68.130)	
0	112(r) Accidental R	elease Prevention (40 Cl	FR 68.130)	

### **US state regulations**

#### California Proposition 65



**WARNING:** This product can expose you to chemicals including Titanium Dioxide: Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Titanium Dioxide (CAS 13463-67-7)Listed: September 2, 2011US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Cristobalite (CAS 14464-46-1) Titanium Dioxide (CAS 13463-67-7)

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date	08-10-2021
Version #	01
Disclaimer	This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
Revision information	Product and Company Identification: Product and Company Identification Composition / Information on Ingredients: After Reaction Composition