HarbisonWalker

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or VERSAFLOW 45 PLUS; VERSAFLOW 45 PLUS WF; VERSAFLOW 45 PLUS H

designation of the mixture

Registration number -

Synonyms None.

Brand Code 2825, 862B, 955B, 4198, 712C

Issue date 24-March-2021

Version number 01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses For Industrial or Professional Use Only

Uses advised against Avoid dry cutting, blasting, or dust generation. Users should be informed of the potential presence

of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under

applicable regulations.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name HarbisonWalker International Limited

Address Dock Road South

Bromborough

Wirral

UK

Division United Kingdom

Telephone General Phone: 44.(0)151.641.5900

e-mail REACH@thinkhwi.com

Contact person HWI USA

1.4. Emergency telephone +44 (0)151 641 5900 (Office hours 07:30 - 17:00)

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary Exposure to powder or dusts may be irritating to eyes, nose and throat. Prolonged exposure may

cause chronic effects. Not classified for health hazards. However, occupational exposure to the

mixture or substance(s) may cause adverse health effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None.

Signal word None.

Hazard statements The mixture does not meet the criteria for classification.

Precautionary statements

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Supplemental label

information

None.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

Material name: VERSAFLOW 45 PLUS; VERSAFLOW 45 PLUS WF; VERSAFLOW 45 PLUS H 2825, 862B, 955B, 4198, 712C Version #: 01 Issue date: 24-March-2021

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Mullite	50 - 70	1302-93-8 215-113-2	-	-	
Classification:					
Cristobalite	10 - 25	14464-46-1 238-455-4	-	-	#
Classification:					
Cement, Alumina, Chemicals	2,5 - 10	65997-16-2 266-045-5	-	-	
Classification:					
Other components below reportable levels	10 - 25				

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

Crystalline silica may be present at low concentrations; most of this is encapsulated in the coarse aggregate or as part of the clays or sands.

SECTION 4: First aid measures

General information Not available.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact **Eye contact** Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. 4.2. Most important Dusts may irritate the respiratory tract, skin and eyes.

symptoms and effects, both

acute and delayed

4.3. Indication of any immediate medical attention

and special treatment

needed

Treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards Not available.

5.1. Extinguishing media

Suitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media

Not available.

5.2. Special hazards arising from the substance or

mixture

Not available.

5.3. Advice for firefighters

Special protective equipment for firefighters

Not available.

Special fire fighting

procedures

Not available.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during personnel clean-up. For personal protection, see section 8 of the SDS.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Avoid the generation of dusts during clean-up. Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. For waste disposal, see section 13 of the SDS.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Minimise dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Practice good housekeeping.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

6 mg/m3

0,1 mg/m3

0,05 mg/m3

6 mg/m3

Total dust.

Total dust.

Respirable dust.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001

8.1. Control parameters

Occupational exposure limits

Amorphous silica (CAS

7631-86-9)

14464-46-1) Fumes, Silica (CAS

69012-64-2)

Cristobalite (CAS

Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	MAK	4 mg/m3	Inhalable fraction.
Cristobalite (CAS 14464-46-1)	MAK	0,15 mg/m3	Respirable dust.
Fumes, Silica (CAS 69012-64-2)	MAK	0,3 mg/m3	Respirable fraction.
Belgium. Exposure Limit Value			
Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	10 mg/m3	
Cristobalite (CAS 14464-46-1)	TWA	0,05 mg/m3	Respirable dust.
Bulgaria. OELs. Regulation No	13 on protection of workers a	against risks of exposure to o	chemical agents at work
Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	10 mg/m3	Inhalable fraction.
		0,07 mg/m3	Respirable fraction.
Fumes, Silica (CAS 69012-64-2)	TWA	10 mg/m3	Inhalable fraction.
		0,07 mg/m3	Respirable fraction.
Mullite (CAS 1302-93-8)	TWA	2 mg/m3	
Croatia. Dangerous Substance 13/09	Exposure Limit Values in the	Workplace (ELVs), Annexes	1 and 2, Narodne Novine,
Components	Туре	Value	Form

MAC

MAC

MAC

Components	Туре	Value	Form	
		0.1 mg/m3	Respirable dust.	

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, a	S
amended.	

Type

Components	Туре	Value
Amorphous silica (CAS 7631-86-9)	TWA	2 mg/m3
Fumes, Silica (CAS 69012-64-2)	TWA	2 mg/m3

Value

Form

Czech Republic. OELs. Government Decree 361 **Components**

Amorphous silica (CAS 7631-86-9)	TWA	4 mg/m3	Dust.
Cristobalite (CAS 14464-46-1)	TWA	0,1 mg/m3	Respirable dust.
Fumes, Silica (CAS 69012-64-2)	TWA	4 mg/m3	Dust.
Denmark. Exposure Limit Values			
_		Value	Form
Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	Type TLV	0,15 mg/m3	Total
Cristobalite (CAS			-

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	2 mg/m3	Fine dust, respiratory fraction
Cristobalite (CAS 14464-46-1)	TWA	0,05 mg/m3	Fine dust, respiratory fraction
Fumes, Silica (CAS 69012-64-2)	TWA	2 mg/m3	Fine dust, respiratory fraction
Mullite (CAS 1302-93-8)	TWA	2 mg/m3	

Finland, Workplace Exposure Limits

Components	Туре	Value	Form	
Amorphous silica (CAS 7631-86-9)	TWA	5 mg/m3		
Cristobalite (CAS 14464-46-1)	TWA	0,05 mg/m3	Respirable.	
Fumes, Silica (CAS 69012-64-2)	TWA	5 mg/m3		
Mullite (CAS 1302-93-8)	TWA	2 mg/m3		

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984 **Components** Type Value Cristobalite (CAS **VME** 0,05 mg/m3 Respirable fraction.

14464-46-1)

69012-64-2)

Regulatory status: Regulatory binding (VRC)

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	4 mg/m3	Inhalable fraction.
Fumes, Silica (CAS 69012-64-2)	TWA	0,3 mg/m3	Respirable fraction.

Germany. TRGS 900, Limit Values in Components	the Ambient Air at the Workplac Type	ce Value	Form
Amorphous silica (CAS 7631-86-9)	AGW	4 mg/m3	Inhalable fraction.
Fumes, Silica (CAS 69012-64-2)	AGW	0,3 mg/m3	Respirable fraction.
Hungary. OELs. Joint Decree on Cher Components	nical Safety of Workplaces Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0,15 mg/m3	Respirable.
Iceland. OELs. Regulation 154/1999 Components	on occupational exposure limits	s Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	5 mg/m3	Respirable dust.
,		10 mg/m3	Total dust.
		0,5 mg/m3	Dust.
Cristobalite (CAS 14464-46-1)	TWA	0,15 mg/m3	Total dust.
		0,05 mg/m3	Respirable dust.
Fumes, Silica (CAS 69012-64-2)	TWA	2 mg/m3	Respirable mist.
Mullite (CAS 1302-93-8)	TWA	2 mg/m3	
Ireland. Occupational Exposure Limit Components	ts Type	Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	6 mg/m3	Total inhalable dust.
		2,4 mg/m3	Respirable dust.
Cristobalite (CAS 14464-46-1)	TWA	0,1 mg/m3	Respirable dust.
Fumes, Silica (CAS 69012-64-2)	TWA	6 mg/m3	Total inhalable dust.
		2,4 mg/m3	Respirable dust.
Italy. Occupational Exposure Limits Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0,025 mg/m3	Respirable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
Latvia. OELs. Occupational exposure Components	limit values of chemical substar Type	nces in work environ Value	ment Form
Amorphous silica (CAS 7631-86-9)	TWA	1 mg/m3	
Cristobalite (CAS 14464-46-1)	TWA	3 fibers/cm3	Fiber.
		1 mg/m3	
Fumes, Silica (CAS 69012-64-2)	TWA	1 mg/m3	
Lithuania. OELs. Limit Values for Cho Components	emical Substances, General Req Type	uirements Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0,05 mg/m3	Respirable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	
Netherlands. OELs (binding) Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0,075 mg/m3	Respirable dust.

or Contaminants in the Workplace Type	Value	Form
TLV	1,5 mg/m3	Respirable dust.
TLV	0,15 mg/m3	Total dust.
	0,05 mg/m3	Respirable dust.
TLV	1,5 mg/m3	Respirable dust.
TWA	2 mg/m3	Respirable fraction.
	_	·
	_	Inhalable fraction.
IWA	0,1 mg/m3	Respirable fraction.
tional exposure to chemical agents (NP 1796)	
Туре	Value	Form
TWA	0,025 mg/m3	Respirable fraction.
TWA	1 mg/m3	Respirable fraction.
00/2007 concerning protection of he Type	ealth in work with c Value	hemical agents
TWA	0,3 mg/m3	
TWA	0,1 mg/m3	
TWA	0,3 mg/m3	
	t risks due to expos	ure to chemicals whil
•	Value	Form
TWA	4 mg/m3	Inhalable fraction.
TWA	0,3 mg/m3	Respirable fraction.
TWA mits	0,3 mg/m3	Respirable fraction.
	0,3 mg/m3 Value	Respirable fraction. Form
mits	· -	·
mits Type	Value 0,05 mg/m3	Form Respirable fraction.
mits Type TWA nt Authority (AV), Occupational Expo	Value 0,05 mg/m3 sure Limit Values (A	Form Respirable fraction. AFS 2015:7)
mits Type TWA nt Authority (AV), Occupational Expo Type	Value 0,05 mg/m3 sure Limit Values (<i>I</i> Value	Form Respirable fraction. AFS 2015:7) Form
Type TWA nt Authority (AV), Occupational Expo Type TWA	Value 0,05 mg/m3 sure Limit Values (A Value) 0,05 mg/m3 1 mg/m3	Form Respirable fraction. AFS 2015:7) Form Respirable dust. Total dust.
Type TWA nt Authority (AV), Occupational Expo Type TWA TWA	Value 0,05 mg/m3 sure Limit Values (A Value 0,05 mg/m3	Form Respirable fraction. AFS 2015:7) Form Respirable dust.
Type TWA THA THA TYPE TYPE TWA TWA TWA TWA TWA TWA TWA	Value 0,05 mg/m3 sure Limit Values (A Value) 0,05 mg/m3 1 mg/m3	Form Respirable fraction. AFS 2015:7) Form Respirable dust. Total dust.
Type TWA THA THA TYPE TYPE TWA TWA TWA TWA TWA TWA TWA TYPE TYPE	Value 0,05 mg/m3 sure Limit Values (A Value 0,05 mg/m3 1 mg/m3 Value	Form Respirable fraction. AFS 2015:7) Form Respirable dust. Total dust. Form
Type TWA TWA TYPE TWA TYPE TWA TWA TWA TWA TWA TYPE TWA TWA TWA TYPE TWA TWA TYPE TWA	Value 0,05 mg/m3 sure Limit Values (Avalue) 0,05 mg/m3 1 mg/m3 Value 0,15 mg/m3	Form Respirable fraction. AFS 2015:7) Form Respirable dust. Total dust. Form Respirable fraction.
	TLV TLV Our and Social Policy on 6 June 2014 of factors in the work environment, Journal Type TWA TWA TWA TWA TWA TWA TWA TW	TLV 0,15 mg/m3 O,05 mg/m3 TLV 1,5 mg/m3 TLV 1,5 mg/m3 TLV 1,5 mg/m3 TLV 1,5 mg/m3 Ture 2014 on the maximum properties in the work environment, Journal of Laws 2014 Type Value TWA 2 mg/m3 TWA 0,1 mg/m3 TWA 0,025 mg/m3 TWA 0,025 mg/m3 TWA 1 mg/m3 TWA 1 mg/m3 TWA 0,3 mg/m3

UK. EH40 Workplace Exposu Components	re Limits (WELs) Type	Value	Form
		2,4 mg/m3	Respirable dust.
Cristobalite (CAS 14464-46-1)	TWA	1 fibers/mL	Fiber.
		5 mg/m3	Fiber.
		0,1 mg/m3	Respirable.
Fumes, Silica (CAS 69012-64-2)	TWA	6 mg/m3	Inhalable dust.
·		2,4 mg/m3	Respirable dust.
EU. OELs, Directive 2004/37	/EC on carcinogen and mutage	ns from Annex III, Part A	
Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0,1 mg/m3	Respirable fraction and dust

Biological limit values

Recommended monitoring

Follow standard monitoring procedures.

No biological exposure limits noted for the ingredient(s).

procedures **Derived no effect levels**

Not available.

(DNELs) **Predicted no effect**

Not available.

concentrations (PNECs)

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the OEL (occupational exposure limit), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation

Individual protection measures, such as personal protective equipment

General information Personal protection equipment should be chosen according to the CEN standards and in discussion

with the supplier of the personal protective equipment.

to keep exposures below the recommended exposure limits.

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear suitable protective clothing.

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels Respiratory protection

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.







Hygiene measures

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Solid. **Form** Powder.

Colour Not available. Odour Not available. **Odour threshold** Not available. pН Not available. Melting point/freezing point Not available. Initial boiling point and Not available.

boiling range

Flash point Not available. Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

(%)

Flammability limit -

upper (%)

Not available.

Vapour pressure Not available. Vapour density Not available. Not available. **Relative density**

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. **Viscosity Explosive properties** Not explosive. **Oxidising properties** Not oxidising.

9.2. Other information No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Contact with incompatible materials.

10.5. Incompatible materials Chlorine, Fluorine,

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not

be specific to industrial application exposure.

10.6. Hazardous

decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Dust may irritate respiratory system. Prolonged inhalation may be harmful.

Skin contact Dust or powder may irritate the skin.

Eve contact Dust may irritate the eyes.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Dusts may irritate the respiratory tract, skin and eyes.

11.1. Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible. Serious eye damage/eye Due to partial or complete lack of data the classification is not possible.

irritation

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible. Skin sensitisation Germ cell mutagenicity Carcinogenicity

Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled. Risk of cancer cannot be excluded with prolonged exposure.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cristobalite (CAS 14464-46-1) 1 Carcinogenic to humans.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible. Specific target organ toxicity Due to partial or complete lack of data the classification is not possible.

- single exposure

Specific target organ toxicity

- repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

This product has no known adverse effect on human health. Other information

SECTION 12: Ecological information

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative

potential

No data available.

Partition coefficient

n-octanol/water (log Kow)

Not available.

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil No data available.

12.5. Results of PBT and

vPvR assessment

Not a PBT or vPvB substance or mixture. Not available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation 12.6. Other adverse effects potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Not available. Contaminated packaging Not available. **EU** waste code Not available.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk

Not applicable.

according to Annex II of MARPOL 73/78 and the IBC

Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU** regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Cristobalite (CAS 14464-46-1)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC)

No 1907/2006, as amended.

Follow national regulation on the protection of workers from the risks of exposure to carcinogens **National regulations**

and mutagens at work, in accordance with Directive 2004/37/EC.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Not available. List of abbreviations References Not available. Information on evaluation method leading to the classification of mixture

Not available.

Full text of any H-statements not written out in full under Sections 2 to 15

None.

Revision information

Product and Company Identification: Product and Company Identification

Composition / Information on Ingredients: Ingredients

Training information

Not available.

Disclaimer

This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.