

## 1. Product and Company Identification

<b>Product identifier</b>	<b>CLIPPER DP</b>	
<b>Version #</b>	01	
<b>Issue date</b>	05-04-2015	
<b>CAS #</b>	Mixture	
<b>Brand Code</b>	5196	
<b>Product use</b>	For Industrial Use Only	
<b>Manufacturer information</b>	HarbisonWalker International 1305 Cherrington Parkway, Suite 100 Moon Township, Pennsylvania 15108 United States <a href="http://www.thinkHWI.com">www.thinkHWI.com</a> General Phone: 412-375-6600 CHEMTREC 24 HOUR 1-800-424-9300 EMERGENCY #	
<b>Supplier</b>	Not available.	

## 2. Hazards Identification

<b>Emergency overview</b>	<b>WARNING</b>  Cancer hazard. Irritating to eyes and skin. Prolonged exposure may cause chronic effects.
<b>Potential health effects</b>	
<b>Routes of exposure</b>	Inhalation. Ingestion. Skin contact. Eye contact.
<b>Eyes</b>	Contact with eyes may cause irritation. Avoid contact with eyes.
<b>Skin</b>	May cause skin irritation. Avoid contact with the skin.
<b>Inhalation</b>	May cause cancer by inhalation. Dusts of this product may cause irritation of the nose, throat, and respiratory tract. Repeated or prolonged inhalation may cause toxic effects. Do not breathe dust. For additional information on inhalation hazards, see Section 11 of this safety data sheet.
<b>Ingestion</b>	Irritating. May cause nausea, stomach pain and vomiting. Do not ingest.
<b>Chronic effects</b>	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis. This product has the potential for generation of respirable dust during handling and use. Dust may contain respirable crystalline silica. Overexposure to dust may result in pneumoconiosis, a respiratory disease caused by inhalation of mineral dust, which can lead to fibrotic changes to the lung tissue, or silicosis, a respiratory disease caused by inhalation of silica dust, which can lead to inflammation and fibrosis of the lung tissue. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.
<b>Signs and symptoms</b>	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
<b>Potential environmental effects</b>	May cause long-term adverse effects in the environment.

## 3. Composition / Information on Ingredients

Components	CAS #	Percent
FIBROUS GLASS	65997-17-3	10 - 30
SILICA, CRYSTALLINE, CRISTOBALITE	14464-46-1	10 - 30
SILICA, CRYSTALLINE, QUARTZ	14808-60-7	1 - 5
Titanium Dioxide	13463-67-7	0.5 - 1.5
Other components below reportable levels		60 - 100

## 4. First Aid Measures

### First aid procedures

#### Inhalation

Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed.

#### Skin contact

Remove and isolate contaminated clothing and shoes. Wash off immediately with soap and plenty of water. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin.

#### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Continue rinsing. Get medical attention if irritation develops and persists.

#### Ingestion

Rinse mouth thoroughly. Never give anything by mouth to a victim who is unconscious or is having convulsions. If ingestion of a large amount does occur, call a poison control center immediately. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

### Notes to physician

In case of shortness of breath, give oxygen. Symptoms may be delayed.

### General advice

In case of shortness of breath, give oxygen. If you feel unwell, seek medical advice (show the label where possible). Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep victim under observation. Keep victim warm.

## 5. Fire Fighting Measures

### Flammable properties

Not available.

### Extinguishing media

#### Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

#### Unsuitable extinguishing media

Not available.

### Fire fighting equipment/instructions

Not available.

### Explosion data

#### Sensitivity to static discharge

Not available.

#### Sensitivity to mechanical impact

Not available.

### Hazardous combustion products

Not available.

## 6. Accidental Release Measures

### Personal precautions

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the MSDS.

### Environmental precautions

Do not contaminate water.

### Methods for containment

Stop leak if you can do so without risk. Prevent entry into waterways, sewer, basements or confined areas.

### Methods for cleaning up

Should not be released into the environment. Avoid the generation of dusts during clean-up. Following product recovery, flush area with water. Clean up in accordance with all applicable regulations. For waste disposal, see section 13 of the MSDS.

### Other information

Clean up in accordance with all applicable regulations.

## 7. Handling and Storage

### Handling

Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not breathe dust. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. When using do not eat or drink. Do not use in areas without adequate ventilation. Wear personal protective equipment. Wash thoroughly after handling. Avoid release to the environment.

### Storage

Store in a closed container away from incompatible materials. Use care in handling/storage. Store away from incompatible materials (see Section 10 of the MSDS).

## 8. Exposure Controls / Personal Protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value	Form
FIBROUS GLASS (CAS 65997-17-3)	TWA	0.2 fibers/cm3	Fiber.
		5 mg/m3	Total particulate.
		5 mg/m3	Fiber, total
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

#### Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
FIBROUS GLASS (CAS 65997-17-3)	TWA	0.2 fibers/cm3	Fiber.
		5 mg/m3	Inhalable fibers.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.

#### Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

#### Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
FIBROUS GLASS (CAS 65997-17-3)	TWA	1 fibers/ml	Respirable fibers.
		5 mg/m3	Inhalable
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value	Form
FIBROUS GLASS (CAS 65997-17-3)	TWA	1 fibers/cm <sup>3</sup>	Fiber.
		10 mg/m <sup>3</sup>	Total dust.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m <sup>3</sup>	Total dust.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m <sup>3</sup>	Respirable dust.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m <sup>3</sup>	Total dust.

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m <sup>3</sup>	Total dust.

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.15 mg/m <sup>3</sup>	Total dust.
		0.05 mg/m <sup>3</sup>	Respirable.
		1.2 mppcf	Respirable.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.3 mg/m <sup>3</sup>	Total dust.
		0.1 mg/m <sup>3</sup>	Respirable.
		2.4 mppcf	Respirable.

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines**

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

**Engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas.

**Personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection**

Wear suitable protective clothing. Wear protective gloves.

**Respiratory protection**

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

**Hand protection**

Wear protective gloves.

**9. Physical & Chemical Properties**

**Appearance**

**Physical state**

Solid.

**Form**

Solid

**Color**

Not available.

**Odor**

Not available.

**Odor threshold**

Not available.

**pH**

Not available.

**Vapor pressure**

Not available.

**Vapor density**

Not available.

**Boiling point**

Not available.

**Melting point/Freezing point**

Not available.

**Solubility (water)**

Not available.

**Specific gravity**

Not available.

<b>Relative density</b>	Not available.
<b>Flash point</b>	Not available.
<b>Flammability limits in air, upper, % by volume</b>	Not available.
<b>Flammability limits in air, lower, % by volume</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Evaporation rate</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.

## 10. Chemical Stability & Reactivity Information

<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Contact with incompatible materials.
<b>Incompatible materials</b>	Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure. Contact your sales representative for clarification.
<b>Hazardous decomposition products</b>	Not available.
<b>Possibility of hazardous reactions</b>	Not available.

## 11. Toxicological Information

<b>Toxicological data</b>	No data available.
<b>Acute effects</b>	Not available.
<b>Sensitization</b>	Not available.
<b>Chronic effects</b>	Hazardous by WHMIS criteria. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.
<b>Carcinogenicity</b>	Hazardous by WHMIS criteria. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) Cancer hazard. According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

### ACGIH Carcinogens

FIBROUS GLASS (CAS 65997-17-3)	A2 Suspected human carcinogen.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	A2 Suspected human carcinogen.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	A2 Suspected human carcinogen.
Titanium Dioxide (CAS 13463-67-7)	A4 Not classifiable as a human carcinogen.

### IARC Monographs. Overall Evaluation of Carcinogenicity

SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	1 Carcinogenic to humans.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	1 Carcinogenic to humans.
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

<b>Skin corrosion/irritation</b>	Not available.
<b>Serious eye damage/irritation</b>	Not available.
<b>Mutagenicity</b>	Not available.
<b>Reproductive effects</b>	Not available.

**Teratogenicity** Not available.  
**Synergistic materials** Not available.

## 12. Ecological Information

**Ecotoxicological data** No ecotoxicity data noted for the ingredient(s).  
**Ecotoxicity** Contains a substance which causes risk of hazardous effects to the environment.  
**Environmental effects** An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
**Aquatic toxicity** Not available.  
**Persistence and degradability** Not available.

## 13. Disposal Considerations

**Disposal instructions** This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

## 14. Transport Information

**TDG** Not regulated as dangerous goods.  
**IATA** Not regulated as dangerous goods.  
**IMDG** Not regulated as dangerous goods.

## 15. Regulatory Information

**Canadian regulations** This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

**WHMIS status** This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves/protective clothing/eye protection. Dust may cause cancer.

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
 A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other Information

### Recommended restrictions

Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

### HMIS® ratings

Health: 2\*  
Flammability: 0  
Physical hazard: 0

### NFPA ratings

Health: 2  
Flammability: 0  
Instability: 0

### Disclaimer

This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Prepared by

Not available.