## **SAFETY DATA SHEET**



## 1. Identification

Product identifier NARSPRAY M-77 B

Other means of identification

Brand Code 0073

Recommended use For Industrial Use Only

**Recommended restrictions** Avoid dry cutting, blasting, or dust generation. Users should be informed of the potential presence

of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under

applicable regulations.

#### Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HarbisonWalker International

Address 1305 Cherrington Parkway, Suite 100

Moon Township, Pennsylvania 15108 US

**Telephone** General Phone: 412-375-6600

Website www.thinkHWI.com Emergency phone number Not available.

## 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1

Serious eye damage/eye irritation Category 1
Carcinogenicity Category 1A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. Causes serious eye damage. May cause cancer.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Wash thoroughly after handling. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. Wash contaminated clothing before reuse.

Storage Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

**Supplemental information**Users should be informed of the potential presence of respirable dust and respirable crystalline

silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and

handling of this material should be provided as required under applicable regulations.

#### 3. Composition/information on ingredients

#### **Mixtures**

| Chemical name                            | Common name and synonyms                 | CAS number | %         |
|------------------------------------------|------------------------------------------|------------|-----------|
| Magnesium Oxide                          |                                          | 1309-48-4  | 60 - 80   |
| Amorphous Silica                         | Fumed Silica<br>Silica, crystalline free | 7631-86-9  | 2.5 - 10  |
| Silica, Fume Undensified                 |                                          | 69012-64-2 | 2.5 - 10  |
| Calcium Oxide                            |                                          | 1305-78-8  | 1 - 2.5   |
| Diiron Trioxide                          |                                          | 1309-37-1  | 1 - 2.5   |
| Expanded Perlite                         |                                          | 93763-70-3 | 1 - 2.5   |
| Kaolin                                   |                                          | 1332-58-7  | 0.1 - 2.5 |
| Quartz (SiO2)                            |                                          | 14808-60-7 | < 0.5     |
| Other components below reportable levels |                                          |            | 20 - 40   |

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Eye contact Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. **General information** 

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters Use fire-extinguishing media appropriate for surrounding materials.

Not available.

Not applicable.

Not available.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Avoid the generation of dusts during clean-up. Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Absorb in vermiculite, dry sand or earth and place into containers. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

#### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

OCIJA Table 7.4 Limite for Air Conteminants (20 CED 4040 4000)

## Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

| US. OSHA Table Z-1 Limits for Aic<br>Components | Type | Value      | Form                 |
|-------------------------------------------------|------|------------|----------------------|
| Calcium Oxide (CAS<br>1305-78-8)                | PEL  | 5 mg/m3    |                      |
| Diiron Trioxide (CAS<br>1309-37-1)              | PEL  | 10 mg/m3   | Fume.                |
| Kaolin (CAS 1332-58-7)                          | PEL  | 5 mg/m3    | Respirable fraction. |
|                                                 |      | 15 mg/m3   | Total dust.          |
| Magnesium Oxide (CAS<br>1309-48-4)              | PEL  | 15 mg/m3   | Total particulate.   |
| Quartz (SiO2) (CAS<br>14808-60-7)               | PEL  | 0.05 mg/m3 | Respirable dust.     |
| US. OSHA Table Z-3 (29 CFR 191                  | •    |            | _                    |
| Components                                      | Туре | Value      | Form                 |
| Amorphous Silica (CAS<br>7631-86-9)             | TWA  | 0.8 mg/m3  |                      |
|                                                 |      | 20 mppcf   |                      |
| Diiron Trioxide (CAS<br>1309-37-1)              | TWA  | 5 mg/m3    | Respirable fraction. |
|                                                 |      | 15 mg/m3   | Total dust.          |
|                                                 |      | 50 mppcf   | Total dust.          |
|                                                 |      | 15 mppcf   | Respirable fraction. |
| Expanded Perlite (CAS<br>93763-70-3)            | TWA  | 5 mg/m3    | Respirable fraction. |
|                                                 |      | 15 mg/m3   | Total dust.          |
|                                                 |      | 50 mppcf   | Total dust.          |
|                                                 |      | 15 mppcf   | Respirable fraction. |
| Kaolin (CAS 1332-58-7)                          | TWA  | 5 mg/m3    | Respirable fraction. |
|                                                 |      | 15 mg/m3   | Total dust.          |
|                                                 |      | 50 mppcf   | Total dust.          |

| Components                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Туре                                                                                                                                                                                                                                                                   | Value                 | Form                 |  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|----------------------|--|
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                        | 15 mppcf              | Respirable fraction. |  |
| Magnesium Oxide (CAS 1309-48-4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | TWA                                                                                                                                                                                                                                                                    | 5 mg/m3               | Respirable fraction. |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                        | 15 mg/m3              | Total dust.          |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                        | 50 mppcf              | Total dust.          |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                        | 15 mppcf              | Respirable fraction. |  |
| Quartz (SiO2) (CAS<br>14808-60-7)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | TWA                                                                                                                                                                                                                                                                    | 0.1 mg/m3             | Respirable.          |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                        | 2.4 mppcf             | Respirable.          |  |
| Silica, Fume Undensified (CAS 69012-64-2)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | TWA                                                                                                                                                                                                                                                                    | 0.8 mg/m3             |                      |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                        | 20 mppcf              |                      |  |
| US. ACGIH Threshold Limi                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                        | Walter                | Form                 |  |
| Components                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Type                                                                                                                                                                                                                                                                   | Value                 | FOIIII               |  |
| Calcium Oxide (CAS<br>1305-78-8)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | TWA                                                                                                                                                                                                                                                                    | 2 mg/m3               |                      |  |
| Diiron Trioxide (CAS<br>1309-37-1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | TWA                                                                                                                                                                                                                                                                    | 5 mg/m3               | Respirable fraction. |  |
| Kaolin (CAS 1332-58-7)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | TWA                                                                                                                                                                                                                                                                    | 2 mg/m3               | Respirable fraction. |  |
| Magnesium Oxide (CAS 1309-48-4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | TWA                                                                                                                                                                                                                                                                    | 10 mg/m3              | Inhalable fraction.  |  |
| Quartz (SiO2) (CAS<br>14808-60-7)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | TWA                                                                                                                                                                                                                                                                    | 0.025 mg/m3           | Respirable fraction. |  |
| US. NIOSH: Pocket Guide                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                        | Walter                | Form                 |  |
| Components                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Туре                                                                                                                                                                                                                                                                   | Value                 | Form                 |  |
| Amorphous Silica (CAS 7631-86-9)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | TWA                                                                                                                                                                                                                                                                    | 6 mg/m3               |                      |  |
| Calcium Oxide (CAS 1305-78-8)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | TWA                                                                                                                                                                                                                                                                    | 2 mg/m3               |                      |  |
| Diiron Trioxide (CAS 1309-37-1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | TWA                                                                                                                                                                                                                                                                    | 5 mg/m3               | Dust and fume.       |  |
| Expanded Perlite (CAS 93763-70-3)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | TWA                                                                                                                                                                                                                                                                    | 5 mg/m3               | Respirable.          |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                        | 10 mg/m3              | Total                |  |
| Kaolin (CAS 1332-58-7)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | TWA                                                                                                                                                                                                                                                                    | 5 mg/m3               | Respirable.          |  |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                        | 10 mg/m3              | Total                |  |
| Quartz (SiO2) (CAS<br>14808-60-7)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | TWA                                                                                                                                                                                                                                                                    | 0.05 mg/m3            | Respirable dust.     |  |
| Silica, Fume Undensified (CAS 69012-64-2)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | TWA                                                                                                                                                                                                                                                                    | 6 mg/m3               |                      |  |
| ogical limit values                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | No biological exposure limits noted                                                                                                                                                                                                                                    | or the ingredient(s). |                      |  |
| osure guidelines                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Occupational exposure to nuisance dust (total and respirable and respirable crystalline silica should be monitored and controlled. |                       |                      |  |
| Good general ventilation (typically 10 air changes per hour) should be used. Ventilation is should be matched to conditions. If applicable, use process enclosures, local exhaust ve or other engineering controls to maintain airborne levels below recommended exposure exposure limits have not been established, maintain airborne levels to an acceptable levengineering measures are not sufficient to maintain concentrations of dust particulates be Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If mateground, cut, or used in any operation which may generate dusts, use appropriate local exposure ventilation to keep exposures below the recommended exposure limits. Eye wash facilities emergency shower must be available when handling this product. |                                                                                                                                                                                                                                                                        |                       |                      |  |

Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

exceeding the exposure limits.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.









General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance** 

Physical state Solid.
Form Powder.
Color Not available.
Odor Not available.
Odor threshold Not available.
Ph Not available.
Melting point/freezing point Not available.
Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Not available.

Vapor pressure
Not available.
Vapor density
Not available.
Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Contact with incompatible materials.

Incompatible materials

Chlorine. Phosphorus.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** Dust may irritate respiratory system. Prolonged inhalation may be harmful.

Skin contactCauses severe skin burns.Eye contactCauses serious eye damage.IngestionCauses digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Coughing.

#### Information on toxicological effects

Acute toxicity Not known.

**Skin corrosion/irritation** Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

#### Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the

overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is

main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and

respirable crystalline silica should be monitored and controlled.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous Silica (CAS 7631-86-9)

3 Not classifiable as to carcinogenicity to humans.

Diiron Trioxide (CAS 1309-37-1)

3 Not classifiable as to carcinogenicity to humans.

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

Silica, Fume Undensified (CAS 69012-64-2)

3 Not classifiable as to carcinogenicity to humans.

## OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Quartz (SiO2) (CAS 14808-60-7) Cancer US. National Toxicology Program (NTP) Report on Carcinogens

#### National Toxicology Program (NTP) Report on Carcinogens

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Developmental effects** 

Quartz (SiO2) 0

**Developmental effects - EU category** 

Quartz (SiO2) 0

**Embryotoxicity** Quartz (SiO2)

Reproductivity Quartz (SiO2) 0

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** 

Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

#### 12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity** 

0

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available. No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions** This product, in its present state, when discarded or disposed of, is not a hazardous waste

according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Since this product is used in several industries, no Waste Code can be provided by the supplier. Hazardous waste code

The Waste Code should be determined in arrangement with your waste disposal partner or the

responsible authority.

Waste from residues / unused

products

Not available.

Contaminated packaging Not available.

#### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA

chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Quartz (SiO2) (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard

Skin corrosion or irritation

categories

Serious eye damage or eye irritation

Carcinogenicity

#### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US** state regulations

#### **California Proposition 65**



WARNING: This product can expose you to chemicals including Glass, Oxide, Chemicals, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

## California Proposition 65 - CRT: Listed date/Carcinogenic substance

Inventory name

Glass, Oxide, Chemicals (CAS 65997-17-3) Listed: July 1, 1990 Nickel (CAS 7440-02-0) Listed: October 1, 1989 Quartz (SiO2) (CAS 14808-60-7) Listed: October 1, 1988 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Australian Inventory of Chemical Substances (AICS)

Magnesium Oxide (CAS 1309-48-4) Quartz (SiO2) (CAS 14808-60-7)

## **International Inventories**

Australia

Country(s) or region

| Canada      | Domestic Substances List (DSL)                                         | No  |
|-------------|------------------------------------------------------------------------|-----|
| Canada      | Non-Domestic Substances List (NDSL)                                    | No  |
| China       | Inventory of Existing Chemical Substances in China (IECSC)             | No  |
| Europe      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No  |
| Europe      | European List of Notified Chemical Substances (ELINCS)                 | No  |
| Japan       | Inventory of Existing and New Chemical Substances (ENCS)               | No  |
| Korea       | Existing Chemicals List (ECL)                                          | No  |
| New Zealand | New Zealand Inventory                                                  | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | No  |
| Taiwan      | Taiwan Chemical Substance Inventory (TCSI)                             | Yes |

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

## 16. Other information, including date of preparation or last revision

Issue date 05-22-2015

Version # 01

United States & Puerto Rico

0073 Version #: 01 Issue date: 05-22-2015

No

On inventory (yes/no)\*

No

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### Disclaimer

This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Material name: NARSPRAY M-77 B