SAFETY DATA SHEET



1. Identification

Product identifier SHOT-TECH 60Z

Other means of identification

Brand Code 433A

Recommended use For Industrial Use Only

Recommended restrictionsUsers should be informed of the potential presence of respirable dust and respirable crystalline

silica as well as their potential hazards. Appropriate training in the proper use and handling of this

material should be provided as required under applicable regulations.

Manufacturer/Supplier information

Manufacturer

Company name HarbisonWalker International

Address 1305 Cherrington Parkway, Suite 100

Moon Township, Pennsylvania 15108 US

Telephone General Phone: 412-375-6600

Website www.thinkHWI.com

Emergency phone number CHEMTREC 24 HOUR 1-800-424-9300

EMERGENCY #

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection.

Response If concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Users should be informed of the potential presence of respirable dust and respirable crystalline

silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and

handling of this material should be provided as required under applicable regulations.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Mullite		1302-93-8	40 - 60
Aluminium Oxide (Non-Fibrous)		1344-28-1	10 - 20

Material name: SHOT-TECH 60Z

Chemical name	Common name and synonyms	CAS number	%
Kyanite		1302-76-7	10 - 20
Silicon Dioxide		7631-86-9	10 - 20
Cement, Alumina, Chemicals		65997-16-2	2.5 - 10
Fumes, Silica		69012-64-2	2.5 - 10
Zircon		14940-68-2	2.5 - 10
Quartz (SiO2)		14808-60-7	1 - 2.5
Titanium Dioxide		13463-67-7	1 - 2.5
Cristobalite		14464-46-1	0.1 - 1
Other components below reportable levels	3		2.5 - 10

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eve contact

Ingestion Rinse mouth. Get medical attention if symptoms occur. Most important Direct contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

If concerned: Get medical advice. Ensure that medical personnel are aware of the material(s) General information

involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters Use fire-extinguishing media appropriate for surrounding materials.

Not available.

Not applicable.

Not available.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Material name: SHOT-TECH 60Z

8. Exposure controls/personal protection

Occupational exposure limits

Components	for Air Contaminants (29 CFR 1910.1000) Type	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
Zircon (CAS 14940-68-2) US. OSHA Table Z-3 (29 CF	PEL R 1910.1000)	5 mg/m3	
Components	Туре	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.15 mg/m3	Total dust.
		0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
Fumes, Silica (CAS 69012-64-2)	TWA	0.8 mg/m3	
0 (0)0=: :=:=		20 mppcf	
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Silicon Dioxide (CAS 7631-86-9)	TWA	0.8 mg/m3	
,		20 mppcf	
US. ACGIH Threshold Limit Components	: Values Type	Value	Form
Aluminium Oxide	TWA	1 mg/m3	Respirable fraction.
(Non-Fibrous) (CAS 1344-28-1)			
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Kyanite (CAS 1302-76-7)	TWA	1 mg/m3	Respirable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Zircon (CAS 14940-68-2)	STEL	10 mg/m3	
	TWA	5 mg/m3	
US. NIOSH: Pocket Guide to		Value	Form
Cristabelita (CAS	Type		
Cristobalite (CAS 14464-46-1)	TWA	3 fibers/cm3	Dust.
		3 fibers/cm3	Fiber.
		5 mg/m3	fibers, total dust
Furnan Ciliaa (CAC	TIA/A	5 mg/m3	Fiber, total
Fumes, Silica (CAS 69012-64-2)	TWA	6 mg/m3	
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Silicon Dioxide (CAS 7631-86-9)	TWA	6 mg/m3	
Zircon (CAS 14940-68-2)	STEL	10 mg/m3	
	TWA	5 mg/m3	
ogical limit values	No biological exposure limits noted for the i	ngredient(s).	

Material name: SHOT-TECH 60Z

SDS US 433A Version #: 01 Issue date: 05-21-2015

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Zirconium silicates (zircon sands) contain trace amounts (106-120 pCi/g) of naturally occurring radioactive uranium and thorium. Overexposure by inhalation to respirable dust containing uranium and thorium may cause lung cancer. Eye contact with the dust may cause eye irritation. Measurements made by Dupont during the use of a similar mineral sand indicated the observance of the 5 mg/m3 OSHA PEL for respirable dust and/or the PEL for quartz ensures the user is below the exposure limits established for uranium and thorium. No LD50 or LC50 can be found for zircon sand.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Use of an impervious apron is recommended.

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Solid

Color Not available.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Acids. Fluorine. Chlorine. Incompatible materials

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure. Contact your sales representative for

clarification.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

No adverse effects due to skin contact are expected. Skin contact Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not available.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica Carcinogenicity

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and

respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cristobalite (CAS 14464-46-1) 1 Carcinogenic to humans.

Fumes, Silica (CAS 69012-64-2) 3 Not classifiable as to carcinogenicity to humans.

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

Silicon Dioxide (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Cristobalite (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

Known To Be Human Carcinogen.

Material name: SHOT-TECH 60Z

Quartz (SiO2) (CAS 14808-60-7)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available. Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

This product, in its present state, when discarded or disposed of, is not a hazardous waste **Disposal instructions**

according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Hazardous waste code Waste from residues / unused

products

Not applicable. Not available.

Not available. Contaminated packaging

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910,1200.

One or more components are not listed on TSCA.

All chemical substances in this product are listed on the TSCA chemical substance inventory

where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Material name: SHOT-TECH 60Z SDS US

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Aluminium Oxide (Non-Fibrous) 1344-28-1	10 - 20

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)

Cristobalite (CAS 14464-46-1) Fumes, Silica (CAS 69012-64-2) Quartz (SiO2) (CAS 14808-60-7) Silicon Dioxide (CAS 7631-86-9)

Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)

Cristobalite (CAS 14464-46-1) Fumes, Silica (CAS 69012-64-2) Quartz (SiO2) (CAS 14808-60-7)

Silicon Dioxide (CAS 7631-86-9)

Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)

Cristobalite (CAS 14464-46-1) Fumes, Silica (CAS 69012-64-2) Quartz (SiO2) (CAS 14808-60-7)

Silicon Dioxide (CAS 7631-86-9)

Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

 Quartz (SiO2) (CAS 14808-60-7)
 Listed: October 1, 1988

 Rutile (TiO2) (CAS 1317-80-2)
 Listed: September 2, 2011

 Titanium Dioxide (CAS 13463-67-7)
 Listed: September 2, 2011

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Material name: SHOT-TECH 60Z SDS US

Country(s) or region Inventory name On inventory (yes/no)* European Inventory of Existing Commercial Chemical Europe Substances (EINECS) Europe European List of Notified Chemical Substances (ELINCS) No Inventory of Existing and New Chemical Substances (ENCS) Japan No Korea Existing Chemicals List (ECL) Yes New Zealand Inventory New Zealand Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances No (PICCS)

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico

16. Other information, including date of preparation or last revision

05-21-2015 Issue date

Version # 01

This information is based on our present knowledge on creation date. However, this shall not Disclaimer

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

Material name: SHOT-TECH 60Z SDS US

No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).