

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

1 Identification

- **Product identifier**
- **Trade name:** SAIRBOND
- **Other means of identification**
- **Article number:** 5001
- **Restrictions** Restricted to industrial or professional use.
- **Application of the substance / the mixture** Refractory Material
- **Uses advised against**
 Avoid dry cutting, blasting, or dust generation. Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 HarbisonWalker International
 2000 Park Lane Drive, Suite 400
 Pittsburgh
 Pennsylvania
 15275
 USA
- **Information department:**
 SDS@thinkHWI.com
 +33 (0)2 59 60 31 14
- **Emergency telephone number:**
 CHEMTREC EMERGENCY
 1-800-424-9300
 US/CAN ONLY

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carcinogenicity 1A

 H350 May cause cancer. Route of exposure:
 Inhalation.

Specific target organ toxicity (repeated exposure) 1H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS07

Skin irritation 2

H315 Causes skin irritation.

Eye irritation 2A

H319 Causes serious eye irritation.

Specific target organ toxicity (single exposure) 3 H335 May cause respiratory irritation.

- **Additional information:**

Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and handling of

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

Trade name: SAIRBOND

(Contd. of page 1)

this material should be provided as required under applicable regulations.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Cristobalite

Silicic acid, sodium salt

Quartz (SiO₂)

· **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H350 May cause cancer. Route of exposure: Inhalation.

H335 May cause respiratory irritation.

H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and handling of

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

Trade name: SAIRBOND

(Contd. of page 2)

this material should be provided as required under applicable regulations.

· **Information pertaining to particular dangers for man and environment:**

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2
 Fire = 0
 Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *2
 Fire = 0
 Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Classification according to (d)(1)(ii) of § 1910.1200**

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

· **Hazards not otherwise classified**

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

1344-09-8	Silicic acid, sodium salt	≥20–≤30%
14464-46-1	Cristobalite	≥10–≤30%
1332-58-7	Kaolin	10%
14808-60-7	Quartz (SiO ₂)	10%
1344-28-1	aluminium oxide	≥1–≤5%

· **Additional information:**

The exact chemical identity and/or percentage (concentration) of the composition has been withheld as a trade secret.

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

Trade name: SAIRBOND

(Contd. of page 3)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** *If symptoms persist consult doctor.*
- **Most important symptoms and effects, both acute and delayed**
Breathing crystalline silica can cause lung disease, including silicosis and lung cancer.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** *Use fire fighting measures that suit the environment.*
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** *Mouth respiratory protective device.*

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
*Mount respiratory protective device.
Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. For personal protection, see section 8 of the SDS.*
- **Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**
*Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.*
- **Reference to other sections**
*See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.*

7 Handling and storage

- **Precautions for safe handling**
*Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions.*
- **Information about protection against explosions and fires:**
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Keep receptacle tightly sealed.*

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

Trade name: SAIRBOND

(Contd. of page 4)

 · **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

 · **Control parameters**

 · **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

14464-46-1 Cristobalite

PEL	Long-term value: 0.05* mg/m ³ *resp. dust; ½ value from resp.dust formulae Quartz
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *respirable particulate matter, A2

1332-58-7 Kaolin

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 2* mg/m ³ E; respirable particulate matter, A4

14808-60-7 Quartz (SiO₂)

PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *respirable particulate matter, A2

1344-28-1 aluminium oxide

PEL	Long-term value: 15*; 5** mg/m ³ *Total dust; ** Respirable fraction
REL	Long-term value: 10* 5** mg/m ³ as Al*Total dust**Respirable/pyro powd./welding f.
TLV	Long-term value: 1* mg/m ³ as Al; *as respirable fraction, A4

 · **Regulatory information**

PEL: Guide to Occupational Exposure Values (OSHA PELs)

REL: Guide to Occupational Exposure Values (NIOSH RELs)

TLV: Guide to Occupational Exposure Values (TLV)

 · **Additional information:**

The lists that were valid during the creation were used as basis.

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

 · **Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

Trade name: SAIRBOND

(Contd. of page 5)

- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes and skin.
- **Breathing equipment:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**
 Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Wear safety glasses with side shields (or goggles).

- **Body protection:**



Standard industrial clothing is sufficient for room temperature installations (ISO 6942). Do not shake out work clothes. Do not remove dust with compressed air.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Solid
- **Color:** According to product specification
- **Odor:** Characteristic
- **Odor threshold:** Not determined.
- **Melting point/Melting range:** Undetermined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

Trade name: SAIRBOND

(Contd. of page 6)

· Boiling point/Boiling range:	Undetermined.
· Flammability:	Not determined.
· Explosion limits:	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable.
· Decomposition temperature:	Not determined.
· pH-value:	Not applicable.
· Viscosity:	
· Kinematic:	Not applicable.
· Dynamic:	Not applicable.
· Solubility in / Miscibility with	
· Water:	Soluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Vapor pressure at 1732 °C (3,149.6 °F):	13.5 hPa (10.1 mm Hg)
· Vapor pressure:	
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not applicable.
· Particle characteristics	Not determined.
· Other information	
· Appearance:	
· Form:	Solid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Solvent content:	
· VOC content:	0.00 %
· Solids content:	53.5–97.5 %
· Change in condition	
· Evaporation rate	Not applicable.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:**
Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

Trade name: SAIRBOND

(Contd. of page 7)

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

1344-09-8 Silicic acid, sodium salt

Oral LD50 3,400 mg/kg (rat)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity** Based on available data, the classification criteria are not met.

· **Specific target organ toxicity - repeated exposure**

Causes damage to lungs through prolonged or repeated exposure.

· **Aspiration hazard** Not applicable

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Interactive effects** No interactive effects between components are known.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

14464-46-1	Cristobalite	1
14808-60-7	Quartz (SiO ₂)	1

· **Additional information**

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However, in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk.." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

· **NTP (National Toxicology Program)**

14464-46-1	Cristobalite	K
14808-60-7	Quartz (SiO ₂)	K

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

Trade name: SAIRBOND

(Contd. of page 8)

- **Alternative sources for toxicological information**
 No non-standard sources for toxicological information where used.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects**
- **Additional ecological information:**
- **General notes:**
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 Since this product is used in several industries, no Waste Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste disposal partner or the responsible authority.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| <ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA | not regulated |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT, IMDG, IATA | not regulated |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT, ADN, IMDG, IATA · Class | not regulated |
| <ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA | not regulated |
| <ul style="list-style-type: none"> · Environmental hazards: | Not applicable. |

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

Trade name: SAIRBOND

(Contd. of page 9)

- | | |
|----------------------------------------------------------------------------------|-----------------|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Special precautions for user | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

1344-28-1 aluminium oxide

- **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

- **Hazardous Air Pollutants**

None of the ingredients is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

14464-46-1 Cristobalite

 14808-60-7 Quartz (SiO₂)

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value)**

14464-46-1 Cristobalite

A2

1332-58-7 Kaolin

A4

 14808-60-7 Quartz (SiO₂)

A2

1344-28-1 aluminium oxide

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14464-46-1 Cristobalite

 14808-60-7 Quartz (SiO₂)

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

Trade name: SAIRBOND

(Contd. of page 10)

Hazard pictograms


GHS07 GHS08

Signal word Danger
Hazard-determining components of labeling:

Cristobalite
 Silicic acid, sodium salt
 Quartz (SiO₂)

Hazard statements

H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H350 May cause cancer. Route of exposure: Inhalation.
 H335 May cause respiratory irritation.
 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

Precautionary statements

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P264 Wash thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P302+P352 If on skin: Wash with plenty of water.
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a poison center/doctor if you feel unwell.
 P321 Specific treatment (see on this label).
 P314 Get medical advice/attention if you feel unwell.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:
Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 10/02/2025

Reviewed on 10/02/2025

Trade name: SAIRBOND

(Contd. of page 11)

16 Other information

This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Contact:** SDS@thinkHWI.com
- **Date of previous version** 10/02/2025
- **Version number of previous version:** 1
- **Date of preparation** 10/02/2025
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - Skin irritation 2: Skin corrosion/irritation – Category 2
 - Eye irritation 2A: Serious eye damage/eye irritation – Category 2A
 - Carcinogenicity 1A: Carcinogenicity – Category 1A
 - Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3
 - Specific target organ toxicity (repeated exposure) 1: Specific target organ toxicity (repeated exposure) – Category 1
- *** Data compared to the previous version altered.**

US