SAFETY DATA SHEET



1. Identification

Product identifier CLEANCOAT 6M

Other means of identification

Brand Code 642A

For Industrial Use Only Recommended use

Users should be informed of the potential presence of respirable dust and respirable crystalline **Recommended restrictions**

silica as well as their potential hazards. Appropriate training in the proper use and handling of this

material should be provided as required under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HarbisonWalker International

Address 1305 Cherrington Parkway, Suite 100

Moon Township, Pennsylvania 15108 US

Telephone General Phone: 412-375-6600

Website www.thinkHWI.com

CHEMTREC 24 HOUR 1-800-424-9300 **Emergency phone number**

EMERGENCY #

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, respiratory Category 1

> Sensitization, skin Category 1 Carcinogenicity Category 1A Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Danger Signal word

Hazard statement May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing

difficulties if inhaled. May cause cancer. Causes damage to organs through prolonged or

repeated exposure.

Precautionary statement

Obtain special instructions before use. Do not handle until all safety precautions have been read Prevention

> and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must

not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

If on skin: Wash with plenty of water. If inhaled: If breathing is difficult, remove person to fresh air Response

and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If experiencing respiratory symptoms: Call a

poison center/doctor. Wash contaminated clothing before reuse.

Storage Store in a manner to minimize airborne dust.

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal**

Hazard(s) not otherwise

classified (HNOC)

None known.

Material name: CLEANCOAT 6M SDS US 1/8

642A Version #: 01 Issue date: 05-01-2018

Supplemental information

Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Magnesium Oxide		1309-48-4	20 - 40
Kaolin		1332-58-7	2.5 - 10
Amorphous Silica	SILICA, AMORPHOUS, FUMED SILICA (CRYSTALLINE FREE)	7631-86-9	1 - 2.5
Quartz (SiO2)		14808-60-7	1 - 2.5
Boric Acid		10043-35-3	0.1 - 1
Nickel		7440-02-0	0.1 - 1
Other components below reportable levels			60 - 80

Crystalline silica may be present at low concentrations; most of this is encapsulated in the coarse aggregate or as part of the clays or sands.

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a

POISON CENTER or doctor/physician.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders. Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Coughing, Difficulty in breathing, May cause an allergic skin reaction, Dermatitis, Rash, Prolonged Most important

symptoms/effects, acute and delayed

Indication of immediate

medical attention and special treatment needed

General information

media

exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Use fire-extinguishing media appropriate for surrounding materials.

Not available.

Specific hazards arising from the chemical

Not applicable.

Special protective equipment and precautions for firefighters Not available.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

Material name: CLEANCOAT 6M 642A Version #: 01 Issue date: 05-01-2018 SDS US

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Ai Components	r Contaminants (29 CFR 1910.1 Type	000) Value	Form
 Kaolin (CAS 1332-58-7)	PEL	5 mg/m3	Respirable fraction.
140111 (0/10 1002 00 1)	1 22	15 mg/m3	Total dust.
Magnesium Oxide (CAS	PEL	15 mg/m3	Total particulate.
1309-48-4)	1 22	ro mg/me	rotal particulate.
Nickel (CAS 7440-02-0)	PEL	1 mg/m3	
Quartz (SiO2) (CAS	PEL	0.05 mg/m3	
14808-60-7)		3	
US. OSHA Table Z-3 (29 CFR 191	0.1000)		
Components	Туре	Value	Form
Amorphous Silica (CAS	TWA	0.8 mg/m3	
7631-86-9)			
		20 mppcf	
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Magnesium Oxide (CAS 1309-48-4)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Quartz (SiO2) (CAS	TWA	0.1 mg/m3	Respirable.
14808-60-7)		5.1 mg/m6	r toophiable.
,		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Value	26		
Components	Туре	Value	Form
Boric Acid (CAS	STEL	6 mg/m3	Inhalable fraction.
10043-35-3)		J	
	TWA	2 mg/m3	Inhalable fraction.
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Magnesium Oxide (CAS	TWA	10 mg/m3	Inhalable fraction.
1309-48-4)		-	
Nickel (CAS 7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	Form
Amorphous Silica (CAS	TWA	6 mg/m3	
7631-86-9)	T\0/0	F / 2	Doonirohla
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable.
NI'-1 -1 (OAO 7440 00 0)	T10/0	10 mg/m3	Total
Nickel (CAS 7440-02-0)	TWA	0.015 mg/m3	
Quartz (SiO2) (CAS	TWA	0.05 mg/m3	Respirable dust.
14808-60-7)			

Material name: CLEANCOAT 6M

SDS US

642A Version #: 01 Issue date: 05-01-2018

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Occupational exposure to nuisance dust (total and respirable)

and respirable crystalline silica should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate.

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.









General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Solid. Form Solid.

Color Not available. Odor Not available. Odor threshold Not available. Not available. Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Not available. Flash point **Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Not available. Vapor pressure Not available. Vapor density

Relative density Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Material name: CLEANCOAT 6M SDS US

642A Version #: 01 Issue date: 05-01-2018

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Phosphorus. Chlorine.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation

may be harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Coughing. Difficulty in breathing. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Boric Acid (CAS 10043-35-3)

Acute Inhalation

LC50 Rat > 0.002 mg/l, 4 Hours

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Material name: CLEANCOAT 6M SDS US

^{*} Estimates for product may be based on additional component data not shown.

Carcinogenicity

In 1997. IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous Silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

2B Possibly carcinogenic to humans. Nickel (CAS 7440-02-0)

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Nickel (CAS 7440-02-0) Reasonably Anticipated to be a Human Carcinogen.

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Developmental effects

Quartz (SiO2) **Developmental effects - EU category** Quartz (SiO2) 0 **Embryotoxicity** 0 Quartz (SiO2) Reproductivity Quartz (SiO2) 0

Specific target organ toxicity -

Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Not an aspiration hazard. **Aspiration hazard**

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be **Chronic effects**

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential Mobility in soil

No data available. No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Hazardous waste code

Since this product is used in several industries, no Waste Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste disposal partner or the

responsible authority.

Waste from residues / unused

products

Not available.

642A Version #: 01 Issue date: 05-01-2018

Material name: CLEANCOAT 6M SDS US Contaminated packaging Not available.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Nickel (CAS 7440-02-0)

Listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Nickel	7440-02-0	0 - 0.1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Nickel (CAS 7440-02-0)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

 Nickel (CAS 7440-02-0)
 Listed: October 1, 1989

 Quartz (SiO2) (CAS 14808-60-7)
 Listed: October 1, 1988

 Titanium Dioxide (CAS 13463-67-7)
 Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Boric Acid (CAS 10043-35-3) Magnesium Oxide (CAS 1309-48-4)

Nickel (CAS 7440-02-0)

Quartz (SiO2) (CAS 14808-60-7)

Material name: CLEANCOAT 6M SDS US

International Inventories

New Zealand

Philippines

Country(s) or region

Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

New Zealand Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Philippine Inventory of Chemicals and Chemical Substances

16. Other information, including date of preparation or last revision

Inventory name

Issue date 05-01-2018

Version # 01

Disclaimer This information is based on our present knowledge on creation date. However, this shall not

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

Revision information Product and Company Identification: Product and Company Identification

Ecological Information: Ecotoxicity

Transport Information: Material Transportation Information

GHS: Classification

Material name: CLEANCOAT 6M

On inventory (yes/no)*

Yes

No

No