

1. Identification

Product identifier	PHANTUM XL087		
Other means of identification			
Brand Code	042B		
Recommended use	For Industrial Use Only		
Recommended restrictions	None known.		
Manufacturer/Supplier information			
Manufacturer			
Company name	HarbisonWalker International		
Address	1305 Cherrington Parkway, Suite 100 Moon Township, Pennsylvania 15108 US		
Telephone	General Phone:	412-375-6600	
Website	www.thinkHWI.com		
Emergency phone number	CHEMTREC 24 HOUR EMERGENCY #	1-800-424-9300	

2. Hazard(s) identification

Classified hazards

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves/protective clothing/eye protection. Dust may cause cancer.

Label elements

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves/protective clothing/eye protection. Dust may cause cancer.

Hazard(s) not otherwise classified (HNOC)

This item is defined as an article per OSHA (29 CFR 1910.1200) and is therefore exempt from labeling. A Safety Data Sheet is available.

This item is not hazardous per OSHA 29 CFR 1910.1200(c). However, individual customer processes (such as grinding, sawing, or blasting) may result in the formation of dust that may present health hazards. May cause respiratory irritation, lung injury, or cancer by inhalation. Limit skin contact. Wash hands after handling. Dispose of waste and residues in accordance with local authority requirements. Wear protective gloves/protective clothing/eye protection. Dust may cause cancer.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Magnesium Oxide		1309-48-4	80 - 90
Aluminium		7429-90-5	2.5 - 10
Graphite		7782-42-5	2.5 - 10
Calcium Oxide		1305-78-8	1 - 2.5
Aluminium Oxide (Non-Fibrous)		1344-28-1	0.1 - 1
Carbon Black		1333-86-4	0.1 - 1
Phenol		108-95-2	0.1 - 1

Chemical name	Common name and synonyms	CAS number	%
Ethane-1,2-diol		107-21-1	0 - 0.1
Formaldehyde		50-00-0	0 - 0.1
Other components below reportable levels			2.5 - 10

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTER or doctor/physician.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.
Eye contact	Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off immediately all contaminated clothing. If concerned: Get medical advice. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	Not available.
Specific hazards arising from the chemical	Not applicable.
Special protective equipment and precautions for firefighters	Not available.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Stop the flow of material, if this is without risk. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Prevent product from entering drains. Following product recovery, flush area with water. Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Do not get in eyes, on skin, or on clothing. Avoid breathing dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	PEL	5 mg/m3 15 mg/m3	Respirable dust. Total dust.
Calcium Oxide (CAS 1305-78-8)	PEL	5 mg/m3	
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Graphite (CAS 7782-42-5)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
Graphite (CAS 7782-42-5)	TWA	15 mppcf

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Calcium Oxide (CAS 1305-78-8)	TWA	2 mg/m3	
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m3 5 mg/m3 10 mg/m3	Welding fume or pyrophoric powder. Respirable. Total
Calcium Oxide (CAS 1305-78-8)	TWA	2 mg/m3	
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m3	
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

The resin binder in this product was specifically engineered to have low toxicity, with minimal free-phenol (less than 100ppm in this refractory product) and no free-formaldehyde. Under certain conditions, thermal decomposition products may still include carbon monoxide, carbon dioxide, formaldehyde, phenol and aromatic and/or aliphatic compounds.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles) and a face shield.
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Solid
Color	Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid	Contact with incompatible materials. Refractories containing crystalline silica may, after service, contain more or less crystalline silica. Care must be taken to avoid and/or control dust from demolition. If in doubt of the proper protection, seek advice from a safety professional. The organic binder in this product falls into a class known as phenolic resin. Refractory products using this type of binder are supplied in two forms, (1) shaped products such as brick and (2) monolithics such as refractory plastics and rams. The hazards associated with phenolic resin are different in the two forms. For pre-cured shapes (brick), the binder has been reacted or polymerized by heat to its solid form prior to shipment. On decomposition by heating, where there is sufficient air and heating rate, the gaseous products are mostly carbon dioxide and water. Under low or limited oxygen supply, decomposition products during heat-up and early service may include phenol, as well as aromatic and/or aliphatic derivatives. After a campaign in service, this refractory product should be completely coked and in that condition the material for disposal would be carbon and an inorganic oxide. During field installation of non-cured unshaped products (monolithics), there is a possibility of exposure to trace amounts of phenol by skin contact and inhalation. After the product has been heated to high temperatures in service, it will have similar decomposition characteristics to pre-cured shapes.
Incompatible materials	Phosphorus. Chlorine. Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure. Contact your sales representative for clarification.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Toxic if inhaled.
Skin contact	Toxic in contact with skin. Causes severe skin burns.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing.

Information on toxicological effects

Acute toxicity	Toxic if inhaled. Toxic in contact with skin.
Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity	Toxic to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of this product.

Bioaccumulative potential**Mobility in soil** No data available.**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.**13. Disposal considerations****Disposal instructions** This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.**Hazardous waste code** Not applicable.**Waste from residues / unused products** Not available.**Contaminated packaging** Not available.**14. Transport information****DOT**

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.**15. Regulatory information****US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA chemical substance inventory where required.**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories** Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical No**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Aluminium	7429-90-5	2.5 - 10

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Massachusetts RTK - Substance List

Aluminium (CAS 7429-90-5)
Calcium Oxide (CAS 1305-78-8)
Carbon Black (CAS 1333-86-4)
Graphite (CAS 7782-42-5)
Magnesium Oxide (CAS 1309-48-4)

US. New Jersey Worker and Community Right-to-Know Act

Aluminium (CAS 7429-90-5)
Calcium Oxide (CAS 1305-78-8)
Carbon Black (CAS 1333-86-4)
Graphite (CAS 7782-42-5)
Magnesium Oxide (CAS 1309-48-4)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminium (CAS 7429-90-5)
Calcium Oxide (CAS 1305-78-8)
Carbon Black (CAS 1333-86-4)
Graphite (CAS 7782-42-5)
Magnesium Oxide (CAS 1309-48-4)

US. Rhode Island RTK

Aluminium (CAS 7429-90-5)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4)	Listed: February 21, 2003
Formaldehyde (CAS 50-00-0)	Listed: January 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-04-2015

Version # 01

Disclaimer This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Revision Information Product and Company Identification: Material Attributes
Transport Information: Material Transportation Information