

1. Identification

Product identifier KAST-O-LITE 26 LI G ON-LINE; KAST-O-LITE 26 LI G ON-LINE WF

Other means of identification

Brand Code 1549, 0907

Recommended use For Industrial Use Only

Recommended restrictions Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HarbisonWalker International
Address 1305 Cherrington Parkway, Suite 100
 Moon Township, Pennsylvania 15108 US

Telephone General Phone: 412-375-6600

Website www.thinkHWI.com

Emergency phone number CHEMTREC 24 HOUR 1-800-424-9300
 EMERGENCY #

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A
 Specific target organ toxicity, repeated exposure Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information Users should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|---|------------|-----------|
| Mullite | | 1302-93-8 | 30 - < 40 |
| Cement, Alumina, Chemicals | | 65997-16-2 | 10 - < 20 |
| Cristobalite | | 14464-46-1 | 10 - < 20 |
| Amorphous Silica | SILICA, AMORPHOUS, FUMED SILICA (CRYSTALLINE FREE) | 7631-86-9 | 5 - < 10 |
| Expanded Perlite | | 93763-70-3 | 5 - < 10 |
| Kaolin | | 1332-58-7 | 3 - < 5 |
| Quartz (SiO ₂) | | 14808-60-7 | 1 - < 3 |
| Titanium Dioxide | | 13463-67-7 | 1 - < 3 |
| Other components below reportable levels | | | 3 - < 5 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|--|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
| Skin contact | Wash off with soap and water. Get medical attention if irritation develops and persists. |
| Eye contact | Rinse with water. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth. Get medical attention if symptoms occur. |
| Most important symptoms/effects, acute and delayed | Prolonged exposure may cause chronic effects. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Use fire-extinguishing media appropriate for surrounding materials. |
| Unsuitable extinguishing media | Not available. |
| Specific hazards arising from the chemical | Not applicable. |
| Special protective equipment and precautions for firefighters | Not available. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| | |
|---|---|
| Precautions for safe handling | Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not breathe dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. |
| Conditions for safe storage, including any incompatibilities | Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---|------|------------------------|----------------------|
| Cristobalite (CAS 14464-46-1) | PEL | 0.05 mg/m ³ | |
| Kaolin (CAS 1332-58-7) | PEL | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |
| Quartz (SiO ₂) (CAS 14808-60-7) | PEL | 0.05 mg/m ³ | |
| Titanium Dioxide (CAS 13463-67-7) | PEL | 15 mg/m ³ | Total dust. |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---|------|------------------------|----------------------|
| Amorphous Silica (CAS 7631-86-9) | TWA | 0.8 mg/m ³ | |
| Cristobalite (CAS 14464-46-1) | TWA | 20 mppcf | |
| | | 0.05 mg/m ³ | Respirable. |
| Expanded Perlite (CAS 93763-70-3) | TWA | 1.2 mppcf | Respirable. |
| | | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |
| | | 50 mppcf | Total dust. |
| Kaolin (CAS 1332-58-7) | TWA | 15 mppcf | Respirable fraction. |
| | | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |
| | | 50 mppcf | Total dust. |
| Quartz (SiO ₂) (CAS 14808-60-7) | TWA | 15 mppcf | Respirable fraction. |
| | | 0.1 mg/m ³ | Respirable. |
| Titanium Dioxide (CAS 13463-67-7) | TWA | 2.4 mppcf | Respirable. |
| | | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |
| | | 50 mppcf | Total dust. |
| | | 15 mppcf | Respirable fraction. |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---|------|-------------------------|----------------------|
| Cristobalite (CAS 14464-46-1) | TWA | 0.025 mg/m ³ | Respirable fraction. |
| Kaolin (CAS 1332-58-7) | TWA | 2 mg/m ³ | Respirable fraction. |
| Mullite (CAS 1302-93-8) | TWA | 1 mg/m ³ | Respirable fraction. |
| Quartz (SiO ₂) (CAS 14808-60-7) | TWA | 0.025 mg/m ³ | Respirable fraction. |
| Titanium Dioxide (CAS 13463-67-7) | TWA | 10 mg/m ³ | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|---|------|------------------------|------------------|
| Amorphous Silica (CAS 7631-86-9) | TWA | 6 mg/m ³ | |
| Expanded Perlite (CAS 93763-70-3) | TWA | 5 mg/m ³ | Respirable. |
| | | 10 mg/m ³ | Total |
| Kaolin (CAS 1332-58-7) | TWA | 5 mg/m ³ | Respirable. |
| | | 10 mg/m ³ | Total |
| Quartz (SiO ₂) (CAS 14808-60-7) | TWA | 0.05 mg/m ³ | Respirable dust. |

| | |
|---|---|
| Biological limit values | No biological exposure limits noted for the ingredient(s). |
| Exposure guidelines | Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. |
| Appropriate engineering controls | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. |

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Use of an impervious apron is recommended.

Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.



General hygiene considerations Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.
Form Solid.
Color Not available.

Odor Not available.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available.

Flammability limit - upper (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Fluorine. Chlorine.
Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not be specific to industrial application exposure.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

| | |
|---|---|
| Amorphous Silica (CAS 7631-86-9) | 3 Not classifiable as to carcinogenicity to humans. |
| Cristobalite (CAS 14464-46-1) | 1 Carcinogenic to humans. |
| Quartz (SiO ₂) (CAS 14808-60-7) | 1 Carcinogenic to humans. |
| Titanium Dioxide (CAS 13463-67-7) | 2B Possibly carcinogenic to humans. |

US. National Toxicology Program (NTP) Report on Carcinogens

Cristobalite (CAS 14464-46-1)

Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

Quartz (SiO₂) (CAS 14808-60-7)

Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Developmental effects

Quartz (SiO₂) 0

Developmental effects - EU category

Quartz (SiO₂) 0

Embryotoxicity

Quartz (SiO₂) 0

Reproductivity

Quartz (SiO₂) 0

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Hazardous waste code Since this product is used in several industries, no Waste Code can be provided by the supplier. The Waste Code should be determined in arrangement with your waste disposal partner or the responsible authority.

Waste from residues / unused products Not available.

Contaminated packaging Not available.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

| | |
|-----------------------------|---|
| Revision date | 02-01-2017 |
| Version # | 02 |
| Disclaimer | This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. |
| Revision information | This document has undergone significant changes and should be reviewed in its entirety. |