SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or THOR 30 ADTECH

designation of the mixture

Registration number

Synonyms None **Brand Code** 7307

24-March-2021 **Issue date**

Version number Λ1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses For Industrial or Professional Use Only

Uses advised against Avoid dry cutting, blasting, or dust generation.

1.3. Details of the supplier of the safety data sheet

Supplier

HarbisonWalker International Limited **Company name**

Address Dock Road South

Bromborough

Wirral UK

Division United Kingdom

General Phone: **Telephone** 44.(0)151.641.5900

e-mail REACH@thinkhwi.com

Contact person HWI USA

1.4. Emergency telephone +44 (0)151 641 5900 (Office hours 07:30 - 17:00)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Hazard summary Prolonged exposure may cause chronic effects. Not classified for health hazards. However,

occupational exposure to the mixture or substance(s) may cause adverse health effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None. Signal word None.

The mixture does not meet the criteria for classification. **Hazard statements**

Precautionary statements

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Dispose of waste and residues in accordance with local authority requirements. **Disposal**

Supplemental label

information

None.

Not a PBT or vPvB substance or mixture. 2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Material name: THOR 30 ADTECH SDS FU

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Mullite	30 - 50	1302-93-8 215-113-2	-	-	
Classification:					
Cement, Alumina, Chemicals	2,5 - 10	65997-16-2 266-045-5	-	-	
Classification: -					
Other components below reportable levels	50 - 70				

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

Crystalline silica may be present at low concentrations; most of this is encapsulated in the coarse aggregate or as part of the clays or sands.

SECTION 4: First aid measures

General information Not available.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important Coughing.

symptoms and effects, both

acute and delayed

4.3. Indication of any Treat symptomatically.

immediate medical attention

and special treatment

needed

SECTION 5: Firefighting measures

General fire hazards Not available.

5.1. Extinguishing media

Suitable extinguishing

Use fire-extinguishing media appropriate for surrounding materials.

media

Unsuitable extinguishing

media

5.2. Special hazards arising

from the substance or

mixture

Not available.

Not available.

5.3. Advice for firefighters

Special protective

Not available.

equipment for firefighters

Special fire fighting Not available.

procedures

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

personnel

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental

precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

7307 Version #: 01 Issue date: 24-March-2021

Material name: THOR 30 ADTECH SDS FU

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure.

7.2. Conditions for safe storage, including any

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

SDS).

incompatibilities 7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	MAK	4 mg/m3	Inhalable fraction.
Fumes, Silica (CAS 69012-64-2)	MAK	0,3 mg/m3	Respirable fraction.
Silicon carbide (CAS 409-21-2)	MAK	5 mg/m3	Respirable fraction.
	STEL	10 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	MAK	5 mg/m3	Respirable dust.
	STEL	10 mg/m3	Respirable dust.
Belgium. Exposure Limit Value	s.		
Components	Туре	Value	
Amorphous silica (CAS 7631-86-9)	TWA	10 mg/m3	
Silicon carbide (CAS 409-21-2)	TWA	10 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	10 mg/m3	Inhalable fraction.
		0,07 mg/m3	Respirable fraction.
Fumes, Silica (CAS 69012-64-2)	TWA	10 mg/m3	Inhalable fraction.
		0,07 mg/m3	Respirable fraction.
Kyanite (CAS 1302-76-7)	TWA	2 mg/m3	
Mullite (CAS 1302-93-8)	TWA	2 mg/m3	
Silicon carbide (CAS 409-21-2)	TWA	5 mg/m3	Inhalable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Respirable dust.

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	MAC	6 mg/m3	Total dust.
		0,1 mg/m3	Respirable dust.
Fumes, Silica (CAS 69012-64-2)	MAC	6 mg/m3	Total dust.
		0,1 mg/m3	Respirable dust.

Material name: THOR 30 ADTECH

SDS EU 7307 Version #: 01 Issue date: 24-March-2021

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine,
13/09

Components	Туре	Value	Form
Silicon carbide (CAS 409-21-2)	MAC	4 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Titanium dioxide (CAS 13463-67-7)	MAC	4 mg/m3	Respirable dust.
		10 mg/m3	Total dust.

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Туре	Value	
Amorphous silica (CAS 7631-86-9)	TWA	2 mg/m3	
Fumes, Silica (CAS 69012-64-2)	TWA	2 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

Czech Republic. OELs. Government Decree 361

Components	Туре	Value	Form	
Amorphous silica (CAS 7631-86-9)	TWA	4 mg/m3	Dust.	
Fumes, Silica (CAS 69012-64-2)	TWA	4 mg/m3	Dust.	
Silicon carbide (CAS 409-21-2)	TWA	5 mg/m3	Dust.	
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Dust.	

Denmark. Exposure Limit Values

Components	Туре	Value	Form	
Fumes, Silica (CAS 69012-64-2)	TLV	2 mg/m3	Respirable.	
Titanium dioxide (CAS 13463-67-7)	TLV	6 mg/m3		

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)

Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	2 mg/m3	Fine dust, respiratory fraction
Fumes, Silica (CAS 69012-64-2)	TWA	2 mg/m3	Fine dust, respiratory fraction
Kyanite (CAS 1302-76-7)	TWA	2 mg/m3	
Mullite (CAS 1302-93-8)	TWA	2 mg/m3	
Silicon carbide (CAS 409-21-2)	TWA	5 mg/m3	Fine dust, respiratory fraction
		10 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	
Finland. Workplace Exposure Li	mits		
Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	5 mg/m3	
Fumes, Silica (CAS 69012-64-2)	TWA	5 mg/m3	
Kyanite (CAS 1302-76-7)	TWA	2 mg/m3	

2 mg/m3

TWA

Material name: THOR 30 ADTECH

Mullite (CAS 1302-93-8)

SDS EU

7307 Version #: 01 Issue date: 24-March-2021

Finland. Workplace Exposure Limits			
Components	Туре	Value	Form
Silicon carbide (CAS 409-21-2)	TWA	0,1 fibers/cm3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Dust.
France. Threshold Limit Value	es (VLEP) for Occupational Exp	osure to Chemicals in Franc	e, INRS ED 984
Components	Tyne	Value	

10 mg/m3

Silicon carbide (CAS VME 409-21-2)

Regulatory status: Indicative limit (VL)

Titanium dioxide (CAS VME 10 mg/m3

13463-67-7)

Regulatory status: Indicative limit (VL)

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	4 mg/m3	Inhalable fraction.
Fumes, Silica (CAS 69012-64-2)	TWA	0,3 mg/m3	Respirable fraction.
Silicon carbide (CAS 409-21-2)	TWA	4 mg/m3	Inhalable dust.
		0,3 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TWA	0,3 mg/m3	Respirable fraction.
Germany. TRGS 900, Limit Val Components	lues in the Ambient Air at the Workplace Type	Value	Form
•			
Amorphous silica (CAS 7631-86-9)	AGW	4 mg/m3	Inhalable fraction.
Fumes, Silica (CAS 69012-64-2)	AGW	0,3 mg/m3	Respirable fraction.
Silicon carbide (CAS 409-21-2)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Fitanium dioxide (CAS 13463-67-7)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Greece. OELs (Decree No. 90/	1999, as amended)		
Components	Туре	Value	Form
Silicon carbide (CAS 409-21-2)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Inhalable
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Inhalable
	on Chemical Safety of Workplaces		
Components	Туре	Value	Form
Silicon carbide (CAS 409-21-2)	TWA	6 mg/m3	Respirable dust.
		10 mg/m3	Total inhalable dust.
Fitanium dioxide (CAS 13463-67-7)	TWA	6 mg/m3	Respirable dust.
		10 mg/m3	Total inhalable dust.

Iceland. OELs. Regulation 154/1999 on Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	5 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
		0,5 mg/m3	Dust.
Fumes, Silica (CAS 69012-64-2)	TWA	2 mg/m3	Respirable mist.
Kyanite (CAS 1302-76-7)	TWA	2 mg/m3	
Mullite (CAS 1302-93-8)	TWA	2 mg/m3	
Fitanium dioxide (CAS 13463-67-7)	TWA	6 mg/m3	
Ireland. Occupational Exposure Limits Components	Туре	Value	Form
Amorphous silica (CAS 7631-86-9)	TWA	6 mg/m3	Total inhalable dust.
		2,4 mg/m3	Respirable dust.
Fumes, Silica (CAS 59012-64-2)	TWA	6 mg/m3	Total inhalable dust.
		2,4 mg/m3	Respirable dust.
Silicon carbide (CAS 409-21-2)	TWA	0,1 fibers/cm3	Respirable dust.
		3 mg/m3	Respirable dust.
		10 mg/m3	Total inhalable dust.
Fitanium dioxide (CAS 13463-67-7)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Total inhalable dust.
Italy. Occupational Exposure Limits Components	Туре	Value	Form
(yanite (CAS 1302-76-7)	TWA	1 mg/m3	Respirable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
Silicon carbide (CAS 109-21-2)	TWA	0,1 fibers/cm3	Fiber.
		3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
		5,	
•	TWA	10 mg/m3	
13463-67-7) Latvia. OELs. Occupational exposure lin		10 mg/m3	ment
13463-67-7) Latvia. OELs. Occupational exposure lin Components Amorphous silica (CAS	nit values of chemical substance:	10 mg/m3	ment
13463-67-7) Latvia. OELs. Occupational exposure lin Components Amorphous silica (CAS 7631-86-9) Fumes, Silica (CAS	nit values of chemical substances Type	10 mg/m3 s in work environ Value	ment
Latvia. OELs. Occupational exposure lin Components Amorphous silica (CAS 7631-86-9) Fumes, Silica (CAS 59012-64-2)	nit values of chemical substances Type TWA	10 mg/m3 s in work environ Value 1 mg/m3	ment
13463-67-7) Latvia. OELs. Occupational exposure lin Components Amorphous silica (CAS 7631-86-9) Fumes, Silica (CAS 69012-64-2) Kyanite (CAS 1302-76-7) Silicon carbide (CAS	nit values of chemical substances Type TWA TWA	10 mg/m3 s in work environ Value 1 mg/m3 1 mg/m3	ment
Latvia. OELs. Occupational exposure lin Components Amorphous silica (CAS 7631-86-9) Fumes, Silica (CAS 69012-64-2) Kyanite (CAS 1302-76-7) Silicon carbide (CAS 409-21-2) Titanium dioxide (CAS	nit values of chemical substances Type TWA TWA TWA	10 mg/m3 s in work environ Value 1 mg/m3 1 mg/m3 2 mg/m3	ment
Latvia. OELs. Occupational exposure lin Components Amorphous silica (CAS 7631-86-9) Fumes, Silica (CAS 69012-64-2) Kyanite (CAS 1302-76-7) Silicon carbide (CAS 409-21-2) Titanium dioxide (CAS 13463-67-7) Lithuania. OELs. Limit Values for Chem	TWA	10 mg/m3 s in work environ Value 1 mg/m3 1 mg/m3 2 mg/m3 6 mg/m3 10 mg/m3	ment
Latvia. OELs. Occupational exposure lin Components Amorphous silica (CAS 7631-86-9) Fumes, Silica (CAS 69012-64-2) Kyanite (CAS 1302-76-7) Silicon carbide (CAS 409-21-2) Titanium dioxide (CAS 13463-67-7) Lithuania. OELs. Limit Values for Chem Components	TWA	10 mg/m3 s in work environ Value 1 mg/m3 1 mg/m3 2 mg/m3 6 mg/m3 10 mg/m3 ements	
13463-67-7) Latvia. OELs. Occupational exposure lin Components Amorphous silica (CAS 7631-86-9) Fumes, Silica (CAS 69012-64-2) Kyanite (CAS 1302-76-7) Silicon carbide (CAS 409-21-2) Titanium dioxide (CAS 13463-67-7) Lithuania. OELs. Limit Values for Chem Components Kyanite (CAS 1302-76-7)	Type TWA	10 mg/m3 s in work environt Value 1 mg/m3 1 mg/m3 2 mg/m3 6 mg/m3 10 mg/m3 ements Value	
Latvia. OELs. Occupational exposure lin Components Amorphous silica (CAS 7631-86-9) Fumes, Silica (CAS 69012-64-2) Kyanite (CAS 1302-76-7) Silicon carbide (CAS 409-21-2) Titanium dioxide (CAS 13463-67-7) Lithuania. OELs. Limit Values for Chem Components Kyanite (CAS 1302-76-7) Mullite (CAS 1302-93-8) Silicon carbide (CAS	TWA	10 mg/m3 s in work environt Value 1 mg/m3 1 mg/m3 2 mg/m3 6 mg/m3 10 mg/m3 ements Value 1 mg/m3	
Titanium dioxide (CAS 13463-67-7) Latvia. OELs. Occupational exposure lin Components Amorphous silica (CAS 7631-86-9) Fumes, Silica (CAS 69012-64-2) Kyanite (CAS 1302-76-7) Silicon carbide (CAS 409-21-2) Titanium dioxide (CAS 13463-67-7) Lithuania. OELs. Limit Values for Chem Components Kyanite (CAS 1302-76-7) Mullite (CAS 1302-93-8) Silicon carbide (CAS 409-21-2)	TWA	10 mg/m3 s in work environt Value 1 mg/m3 1 mg/m3 2 mg/m3 6 mg/m3 10 mg/m3 ements Value 1 mg/m3 1 mg/m3	Form

Lithuania. OELs. Limit Values f Components	Type	Value	Form
		1 mg/m3	Dust.
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	
Norway. Administrative Norms Components	for Contaminants in the Wor Type	kplace Value	Form
Amorphous silica (CAS 7631-86-9)	TLV	1,5 mg/m3	Respirable dust.
Fumes, Silica (CAS 69012-64-2)	TLV	1,5 mg/m3	Respirable dust.
Silicon carbide (CAS 409-21-2)	TLV	0,1 fibers/cm3	Fiber.
		0,5 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TLV	5 mg/m3	
Ordinance of the Minister of La and intensities of harmful heal Components			
Amorphous silica (CAS 7631-86-9)	TWA	2 mg/m3	Respirable fraction.
. 332 33 31		10 mg/m3	Inhalable fraction.
Silicon carbide (CAS 409-21-2)	TWA	10 mg/m3	Inhalable fraction.
Titanium dioxide (CAS 13463-67-7)	STEL	30 mg/m3	
ŕ	TWA	10 mg/m3	Inhalable fraction.
Portugal. VLEs. Norm on occup Components	ational exposure to chemical Type	agents (NP 1796) Value	Form
Kyanite (CAS 1302-76-7)	TWA	1 mg/m3	Respirable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
Silicon carbide (CAS 409-21-2)	TWA	0,1 fibers/cm3	Respirable fibers.
		3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Romania. OELs. Protection of v Components	vorkers from exposure to che Type	mical agents at the workplac Value	e
Titanium dioxide (CAS 13463-67-7)	STEL	15 mg/m3	
	TWA	10 mg/m3	
Slovakia. OELs. Regulation No. Components	300/2007 concerning protec Type	tion of health in work with cl Value	nemical agents Form
	TWA	0,3 mg/m3	
Amorphous silica (CAS 7631-86-9) Fumes, Silica (CAS 69012-64-2)	TWA	0,3 mg/m3	
7631-86-9) Fumes, Silica (CAS	TWA	0,3 mg/m3 4 mg/m3	Inhalable fraction.
7631-86-9) Fumes, Silica (CAS 69012-64-2) Silicon carbide (CAS		· -	Inhalable fraction. Respirable fraction.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

TWA TWA TWA TWA TWA TWA TYPE TWA	4 mg/m3 0,3 mg/m3 10 mg/m3 1,25 mg/m3 1,25 mg/m3 Value 3 mg/m3 10 mg/m3 10 mg/m3	Inhalable fraction. Respirable fraction. Inhalable fraction. Respirable fraction. Inhalable fraction. Respirable fraction. Form Respirable fraction. Inhalable fraction.
TWA TWA Sure Limits Type TWA	10 mg/m3 1,25 mg/m3 10 mg/m3 1,25 mg/m3 Value 3 mg/m3 10 mg/m3	Inhalable fraction. Respirable fraction. Inhalable fraction. Respirable fraction. Form Respirable fraction.
TWA sure Limits Type TWA	1,25 mg/m3 10 mg/m3 1,25 mg/m3 Value 3 mg/m3 10 mg/m3	Respirable fraction. Inhalable fraction. Respirable fraction. Form Respirable fraction.
sure Limits Type TWA	10 mg/m3 1,25 mg/m3 Value 3 mg/m3 10 mg/m3	Inhalable fraction. Respirable fraction. Form Respirable fraction.
sure Limits Type TWA	1,25 mg/m3 Value 3 mg/m3 10 mg/m3	Respirable fraction. Form Respirable fraction.
Type TWA	Value 3 mg/m3 10 mg/m3	Form Respirable fraction.
Type TWA	3 mg/m3 10 mg/m3	Respirable fraction.
TWA	3 mg/m3 10 mg/m3	Respirable fraction.
	10 mg/m3	·
TWA	5.	Tillialable fraction.
TWA	10 mg/ms	
onment Authority (AV), Occupation	onal Exposure Limit Values (AFS 2015:7)
Туре	. Value	Form
TWA	1 mg/m3	Total dust.
TWA	1 mg/m3	Total dust.
TWA	0,2 fibers/mL	
TWA	5 mg/m3	Total dust.
erte am Arbeitsplatz		
Туре	Value	Form
TWA	0,3 mg/m3	Respirable fume.
TWA	3 mg/m3	Respirable dust.
	10 mg/m3	Inhalable dust.
TWA	3 mg/m3	Respirable dust.
		F
		Form
TWA	6 mg/m3	Inhalable dust.
	2,4 mg/m3	Respirable dust.
TWA	6 mg/m3	Inhalable dust.
	2.4 ma/m3	Respirable dust.
TWA	· -	Respirable.
	-	. copii doioi
	10 mg/m3	Inhalable
TWA	4 mg/m3	Respirable.
	10 mg/m3	Inhalable
No biological exposure limits noted for	or the ingredient(s).	
Follow standard monitoring procedure	res.	
Not available.		
	Type TWA TWA TWA TWA TWA Verte am Arbeitsplatz Type TWA TWA TWA TWA TWA TWA TWA TW	TWA 1 mg/m3 TWA 0,2 fibers/mL TWA 5 mg/m3 Ferte am Arbeitsplatz Type Value TWA 0,3 mg/m3 TWA 0,3 mg/m3 TWA 3 mg/m3 TWA 3 mg/m3 TWA 3 mg/m3 TWA 6 mg/m3 TWA 6 mg/m3 TWA 6 mg/m3 TWA 6 mg/m3 TWA 4 mg/m3 TWA 4 mg/m3 TWA 4 mg/m3 No biological exposure limits noted for the ingredient(s). Follow standard monitoring procedures.

Material name: THOR 30 ADTECH

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information Personal protection equipment should be chosen according to the CEN standards and in discussion

with the supplier of the personal protective equipment.

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear suitable protective clothing.

Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.







Hygiene measures

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Solid. **Form** Solid

Colour Not available. Odour Not available. **Odour threshold** Not available. Not available. Melting point/freezing point Not available. Initial boiling point and Not available.

boiling range

Flash point Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Flammability limit -

upper (%)

Not available.

Vapour pressure Not available. Vapour density Not available. **Relative density** Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Material name: THOR 30 ADTECH SDS FU

7307 Version #: 01 Issue date: 24-March-2021

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **Viscosity Explosive properties** Not explosive. Oxidising properties Not oxidising.

9.2. Other information No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Contact with incompatible materials.

Chlorine. Fluorine. 10.5. Incompatible materials

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not

be specific to industrial application exposure.

10.6. Hazardous decomposition products

10.4. Conditions to avoid

No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Coughing. 11.1. Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation

Serious eye damage/eye

irritation

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Respiratory sensitisation

Skin sensitisation

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica Carcinogenicity inhaled from occupational sources can cause lung cancer in humans. However in making the

overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on

external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU

Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and

controlled. Risk of cancer cannot be excluded with prolonged exposure.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity

- single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity

repeated exposure

Material name: THOR 30 ADTECH

Due to partial or complete lack of data the classification is not possible.

7307 Version #: 01 Issue date: 24-March-2021

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

This product has no known adverse effect on human health. Other information

SECTION 12: Ecological information

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative

potential

No data available.

Not available. **Partition coefficient**

n-octanol/water (log Kow)

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil No data available.

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture. Not available.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Not available. Contaminated packaging Not available. **EU** waste code Not available.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not applicable.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Material name: THOR 30 ADTECH SDS FU Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as

amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulationsThe product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC)

No 1907/2006, as amended.

National regulations Follow national regulation on the protection of workers from the risks of exposure to carcinogens

and mutagens at work, in accordance with Directive 2004/37/EC.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviationsNot available.ReferencesNot available.Information on evaluationNot available.

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any H-statements

not written out in full under

Sections 2 to 15

None.

Revision information Product and Company Identification: Product and Company Identification

Training information Not available.

Disclaimer This information is based on our present knowledge on creation date. However, this shall not

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.