

Safety Data Sheet
acc. to OSHA HCS

Date of issue: 03/24/2025

Reviewed on 03/24/2025

1 Identification

- **Product identifier**
- **Trade name:** SPARCON 32 C
- **Other means of identification**
- **Article number:** 699D
- **Restrictions** Restricted to industrial or professional use.
- **Application of the substance / the mixture** Refractory Material
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
HarbisonWalker International
2000 Park Lane Drive, Suite 400
Pittsburgh
Pennsylvania
15275
USA
- **Information department:**
SDS.information@calderys.com
+33 1 49 55 38 57
- **Emergency telephone number:**
CHEMTREC EMERGENCY
1-800-424-9300
US/CAN ONLY

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Carcinogenicity 1A

H350 May cause cancer. Route of exposure: Inhalation.

Specific target organ toxicity (repeated exposure) 1H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.



GHS07

Eye irritation 2A

H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07



GHS08

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 03/24/2025

Reviewed on 03/24/2025

Trade name: SPARCON 32 C

(Contd. of page 1)

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

Quartz (SiO₂)
 silicon dioxide, amorphous

- **Hazard statements**

H319 Causes serious eye irritation.
 H350 May cause cancer. Route of exposure: Inhalation.
 H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

- **Precautionary statements**

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P264 Wash thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P314 Get medical advice/attention if you feel unwell.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Information pertaining to particular dangers for man and environment:**

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2
 Fire = 0
 Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *2
 Fire = 0
 Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

- **Classification according to (d)(1)(ii) of § 1910.1200**

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

- **Hazards not otherwise classified**

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

US

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Date of issue: 03/24/2025

Reviewed on 03/24/2025

Trade name: SPARCON 32 C

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1344-28-1	aluminium oxide	7–13%
7631-86-9	silicon dioxide, amorphous	3–7%
65997-16-2	Alumina cement	3–7%
14808-60-7	Quartz (SiO ₂)	1–5%

- **Additional information:**

The exact chemical identity and/or percentage (concentration) of the composition has been withheld as a trade secret.

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed**
Breathing crystalline silica can cause lung disease, including silicosis and lung cancer.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 03/24/2025

Reviewed on 03/24/2025

Trade name: SPARCON 32 C

(Contd. of page 3)

· Protective Action Criteria for Chemicals

· PAC-1:

1344-28-1	aluminium oxide	15 mg/m ³
1302-76-7	Kyanite (aluminum silicate)	3 mg/m ³
7631-86-9	silicon dioxide, amorphous	18 mg/m ³
69012-64-2	Silica-Amorphous Silica fume	45 mg/m ³
14808-60-7	Quartz (SiO ₂)	0.075 mg/m ³
1309-48-4	magnesium oxide	30 mg/m ³

· PAC-2:

1344-28-1	aluminium oxide	41 ppm
1302-76-7	Kyanite (aluminum silicate)	33 mg/m ³
7631-86-9	silicon dioxide, amorphous	200 ppm
69012-64-2	Silica-Amorphous Silica fume	500 mg/m ³
14808-60-7	Quartz (SiO ₂)	8.3 mg/m ³
1309-48-4	magnesium oxide	120 mg/m ³

· PAC-3:

1344-28-1	aluminium oxide	240 ppm
1302-76-7	Kyanite (aluminum silicate)	200 mg/m ³
7631-86-9	silicon dioxide, amorphous	1200 ppm
69012-64-2	Silica-Amorphous Silica fume	3,000 mg/m ³
14808-60-7	Quartz (SiO ₂)	50 mg/m ³
1309-48-4	magnesium oxide	730 mg/m ³

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions.

· Information about protection against explosions and fires:

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

US

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Date of issue: 03/24/2025

Reviewed on 03/24/2025

Trade name: SPARCON 32 C

(Contd. of page 4)

8 Exposure controls/personal protection

- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

1344-28-1 aluminium oxide

PEL	Long-term value: 15*; 5** mg/m ³ *Total dust; ** Respirable fraction
REL	Long-term value: 10* 5** mg/m ³ as Al*Total dust**Respirable/pyro powd./welding f.
TLV	Long-term value: 1* mg/m ³ as Al; *as respirable fraction, A4

69012-64-2 Silica-Amorphous Silica fume

TLV TLV withdrawn

14808-60-7 Quartz (SiO₂)

PEL	Long-term value: 0.05* mg/m ³ *resp. dust; 30mg/m ³ /%SiO ₂ +2
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *respirable particulate matter, A2

- **Regulatory information**
PEL: Guide to Occupational Exposure Values (OSHA PELs)
REL: Guide to Occupational Exposure Values (NIOSH RELs)
TLV: Guide to Occupational Exposure Values (TLV)
- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**
Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 03/24/2025

Reviewed on 03/24/2025

Trade name: SPARCON 32 C

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses

· **Body protection:**



Standard industrial clothing is sufficient for room temperature installations (ISO 6942). Do not shake out work clothes. Do not remove dust with compressed air.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Solid

· **Color:**

Grey

· **Odor:**

uncharacteristic

· **Odor threshold:**

Not determined.

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

Undetermined.

· **Flammability:**

Not determined.

· **Explosion limits:**

· **Lower:**

Not determined.

· **Upper:**

Not determined.

· **Flash point:**

Not applicable.

· **Auto igniting:**

>370 °C (>698 °F)

· **Decomposition temperature:**

Not determined.

· **pH-value:**

Not applicable.

· **Viscosity:**

· **Kinematic:**

Not applicable.

· **Dynamic:**

Not applicable.

· **Solubility in / Miscibility with**

· **Water:**

Soluble.

· **Partition coefficient (n-octanol/water):**

Not determined.

· **Vapor pressure:**

Not applicable.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 03/24/2025

Reviewed on 03/24/2025

Trade name: SPARCON 32 C

(Contd. of page 6)

- **Vapor pressure:**
 - **Density:** Not determined.
 - **Relative density** Not determined.
 - **Vapor density** Not applicable.
 - **Particle characteristics** Not determined.
-
- **Other information**
 - **Appearance:**
 - **Form:** Solid in various forms
 - **Important information on protection of health and environment, and on safety.**
 - **Ignition temperature:** Product is not selfigniting.
 - **Danger of explosion:** Product does not present an explosion hazard.
 - **Solvent content:**
 - **VOC content:** 0.00 %
 - **Solids content:** 100.0 %
 - **Change in condition**
 - **Evaporation rate** Not applicable.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
- **Interactive effects** No interactive effects between components are known.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

7631-86-9	silicon dioxide, amorphous	3
14808-60-7	Quartz (SiO ₂)	1

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 03/24/2025

Reviewed on 03/24/2025

Trade name: SPARCON 32 C

(Contd. of page 7)

· NTP (National Toxicology Program)

 14808-60-7 Quartz (SiO₂)

K

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

12 Ecological information

· Toxicity

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

· Other adverse effects
· Additional ecological information:
· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

· Waste treatment methods
· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:
· Recommendation: Disposal must be made according to official regulations.

· Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number
· DOT, IMDG, IATA

not regulated

· UN proper shipping name
· DOT, IMDG, IATA

not regulated

· Transport hazard class(es)
· DOT, ADN, IMDG, IATA
· Class

not regulated

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 03/24/2025

Reviewed on 03/24/2025

Trade name: SPARCON 32 C

(Contd. of page 8)

- | | |
|--|-----------------|
| · Packing group | |
| · DOT, IMDG, IATA | not regulated |
| · Environmental hazards: | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Special precautions for user | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

1344-28-1 aluminium oxide

TSCA (Toxic Substances Control Act):

1344-28-1	aluminium oxide	ACTIVE
1302-76-7	Kyanite (aluminum silicate)	ACTIVE
92704-41-1	Chamotte	ACTIVE
7631-86-9	silicon dioxide, amorphous	ACTIVE
65997-16-2	Alumina cement	ACTIVE
69012-64-2	Silica-Amorphous Silica fume	ACTIVE
14808-60-7	Quartz (SiO ₂)	ACTIVE
1309-48-4	magnesium oxide	ACTIVE
7558-80-7	Sodium dihydrogen phosphate	ACTIVE
	inert component	ACTIVE

Hazardous Air Pollutants

None of the ingredients is listed.

Proposition 65
Chemicals known to cause cancer:

 14808-60-7 Quartz (SiO₂)

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 03/24/2025

Reviewed on 03/24/2025

Trade name: SPARCON 32 C

(Contd. of page 9)

· Carcinogenic categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

1344-28-1	aluminium oxide	A4
14808-60-7	Quartz (SiO ₂)	A2
1309-48-4	magnesium oxide	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7	Quartz (SiO ₂)
------------	----------------------------

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms


GHS07 GHS08

· Signal word *Danger*
· Hazard-determining components of labeling:

 Quartz (SiO₂)

silicon dioxide, amorphous

· Hazard statements

H319 Causes serious eye irritation.

H350 May cause cancer. Route of exposure: Inhalation.

H372 Causes damage to the lung through prolonged or repeated exposure. Route of exposure: Inhalation.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:
· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

(Contd. on page 11)

Safety Data Sheet acc. to OSHA HCS

Date of issue: 03/24/2025

Reviewed on 03/24/2025

Trade name: SPARCON 32 C

(Contd. of page 10)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Contact:** sds.information@calderys.com
- **Date of previous version** 03/24/2025
- **Version number of previous version:** 1
- **Date of preparation** 03/24/2025

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Eye irritation 2A: Serious eye damage/eye irritation – Category 2A

Carcinogenicity 1A: Carcinogenicity – Category 1A

Specific target organ toxicity (repeated exposure) 1: Specific target organ toxicity (repeated exposure) – Category 1

- *** Data compared to the previous version altered.**